District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Date: 01/15/19

□ Original

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe. NM 87505

Dulla 1 0, 1111 07505	
GAS CAPTURE PLAN	JAN 3 UZUIA VZS RECEIVED
Operator & OGRID No.: Mewbou	urne Oil Company - 14744

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility - Name of facility

☐ Amended - Reason for Amendment:___

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Pronghorn 15 B3BO Fed Com #1H	30-025-43903	B-15-23S-34E	185 FNL & 1700 FEI.	0	NA	ONLINE AFTER FRAC
·						·

Catl	herino	System	and	Pinelin	e No	tifica	tion
\J414 1		CTTTLL					LIUII

Well(s) will be connected to a production facility after flowback operations are complete,	if gas transporter system is in
place. The gas produced from production facility is dedicated to <u>Lucid</u>	and will be connected to
low/high pressure gathering system located in Lea County, N	New Mexico. It will require
4665 of pipeline to connect the facility to low/high pressure gathering system. Mey	wbourne Oil Company provides
(periodically) to Lucid a drilling, completion and estimated first production date	te for wells that are scheduled to
be drilled in the foreseeable future. In addition, Mewbourne Oil Company and Lucid	have periodic
conference calls to discuss changes to drilling and completion schedules. Gas from the	
Lucid Processing Plant located in Sec. 25, Twn. 188, Rng. 25E,	
The actual flow of the gas will be based on compression operating parameters and gathering systematical systems.	em pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Gas Wransporter system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines