District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department Oil Conservation Division HOBBS

Santa Fe, NM 87505

Oil Conservation Division 1220 South St. Francis Dr. MAY 3 0 2019

Submit Original to Appropriate District Office

GAS CAPTURE PLAN

	_	_		
RE	_			u
			ıw	
-	u	_		
	_	_		

x Original	Operator & OGRID No.:	Devon Production Co., L.P. (6137)		
☐ Amended		Date:_	10/16/2018	
Reason for Amendment:				
(

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

Well(s)/Production Facility - Rattlesnake MDP 1 CTB 20-9

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location.	Footages	Expected	Flared	or	Comments
		(ULSTR)		MCF/D	Vented		
Green Wave 20-32 Fed 2H		Sec 20-T26S-R34E	2456' FSL 301' FWL				Will connect to Rattlesnake MDP 1 CTB 20-9
Green Wave 20-32 Fed 7H		Sec 20-T26S-R34E	2456'FSL 331' FWL				Will connect to Rattlesnake MDP 1 CTB 20-9
Green Wave 20-32 Fed 11H	-46093	Sec 20-T26S-R34E	2456'FSL 361' FWL				Will connect to Rattlesnake MDP 1 CTB 20-9
Green Wave 20-32 Fed 15H		Sec 20-T26S-R34E	2456'FSL 271' FWL				Will connect to Rattlesnake MDP 1 CTB 20-9

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Enterprise South Eddy and will be connected to Enterprise Iow/high pressure gathering system located in Eddy County, New Mexico. It will require <a href="Moleon of Production of Production

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Enterprise's system at that time. Based on current information, it is Devon's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines