. •					
Form 3160-5 (June 2015) UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT				FORM APPROVED OMB NO. 1004-0137 / Expires: January 31, 2018	
SUNDRY NOTICES AND REPORTS ON WELLS			OCD	5. Lease Serial No. NMNM123532	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-eeting BBS OCD abandoned well. Use form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name	
SUBMIT IN	TRIPLICATE - Other instruct	tions on page 2JUN 🍟		7. If Unit or CA/Agree	ment, Name and/or No.
1. Type of Well Soli Well Gas Well Oth	her	RECI	EIVED	8. Well Name and No. BASEBALL CAP F	EDERAL COM 607H
2. Name of Operator COG OPERATING LLC	YTE X REYES	9. API Well No. 30-025-45786-00-X1			
3a. Address ONE CONCHO CENTER 60 MIDLAND, TX 79701-4287	Phone No. (include area code) : 575-748-6945	a code) 10. Field and Pool or Exploratory Area WILDCAT BONE SPRING			
4. Location of Well (Footage, Sec., 7	C., R., M., or Survey Description)	· · · ·		11. County or Parish, S	itate
Sec 25 T24S R34E SWSW 34 32.182133 N Lat, 103.428909			LEA COUNTY, I	M	
12. CHECK THE AI	PPROPRIATE BOX(ES) TO	INDICATE NATURE O	F NOTICE,	REPORT, OR OTH	ER DATA
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	C Acidize	Deepen	Producti	on (Start/Resume)	UWater Shut-Off
Subsequent Report	□ Alter Casing	Hydraulic Fracturing	C Reclama		□ Well Integrity
	Casing Repair	■ New Construction			Other Change to Original A
Final Abandonment Notice	Change Plans	Plug and Abandon Plug Back	U Tempora	arily Abandon isposal	PD
following completion of the involved testing has been completed. Final At determined that the site is ready for f COG Operating respectfully re APD. Surface Drill 14.75? hole to 1,305? Set 10.75? 45.5# L80 BTC ca Cement in one stage to surfac Lead: 550 sx of Class C + 6% Tail: 200 sx of Class C + 1% (The Operator respectfully requ	bandonment Notices must be filed on inal inspection. equests approval for the follow ssing @ 1,305? ce: o gel (13.5 ppg / 1.75 cuft/ sx) CaCl2 (14.8 ppg/ 1.35 cuft/sx)	ly after all requirements, includi	ing reclamation	h, have been completed a	id the operator has
14. I hereby certify that the foregoing is Co Name (Printed/Typed) MAYTE X	Electronic Submission #4621 For COG OPE mmitted to AFMSS for process	RATING LLC, sent to the H ing by ZOTA STEVENS on	lobbs	9ZS0030SE)	
Signature (Electronic S	Submission)	Date 04/22/20	019		· · · · · · · · · · · · · · · · · · ·
	THIS SPACE FOR F	EDERAL OR STATE		SE	<u></u> .
<u>Approved By</u> ZOTA STEVENS Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent which would entitle the applicant to condu	varrant or ect lease Office Hobbs	UM ENGINE	ER	Date 04/24/2019	
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a crime statements or representations as to an	e for any person knowingly and y matter within its jurisdiction.	willfully to ma	ke to any department or a	agency of the United
(Instructions on page 2) ** BLM REV	ISED ** BLM REVISED **	BLM REVISED ** BLM	I REVISED	** BLM REVISED)** KZ

.

Additional data for EC transaction #462180 that would not fit on the form

32. Additional remarks, continued

Description of operations

1. Spudder rig will move in to drill the surface hole and pre-set surface casing on the well. a. After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations)

b. The spudder rig will utilize fresh water-based mud to drill the surface hole to TD.
Solids control will be handled entirely on a closed loop basis. No earth pits will be used.
2. The wellhead will be installed and tested as soon as the surface casing is cut off and the WOC time has been reached.

3. A blind flange at the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with needle valves installed on the wing valve.
4. Spudder rig operations are expected to take 2-3 days per well on the pad.

5. The BLM will be contacted and notified 24 hours prior to commencing spudder rig operations. 6. Drilling operations will begin with a larger rig and a BOP stack equal to or greater than the pressure rating that was permitted will be nippled up and tested on the wellhead before drilling operations resume on each well.

a. The larger rig will move back onto the location with 90 days from the point at which the wells are secured and spudder rig is moved off location.

b. The BLM will be contacted / notified 24 hours before the larger rig moves back on the pre-set locations

7. Operator will have supervision on the rig to ensure compliance with all BLM and NMOCD regulations and to oversee operations.

8. Once the rig is removed, Operator will secure the wellhead area by placing a 1 inch steel plate over the cellar and wellhead.

Intermediate 5M BOP System Drill 9.875? hole to 12,105? Set 7.625? 29.7# HCL-80 BTC @ 12,105? Cement in two stages to surface with DV tool and ECP @ 5,525? First Stage: Lead: 700 sx of Halliburton NeoCem (11.0 ppg / 2.81 cuft/ sx) Tail: 300 sx of Class H (16.4 ppg/ 1.10 cuft/sx) Second Stage: Lead: 900 sx of Halliburton NeoCem (11.0 ppg / 2.81 cuft/ sx) Tail: 150 sx of Class C + 2% CaCl2 (14.8 ppg/ 1.35 cuft/sx) Production

10M BOP System (5M Annular variance approved with original APD) Drill 6.75? hole to 22,750? Set 5.5? 23# P110 BTC from 0? to 11,605? (500? inside intermediate casing) Set 5.5? 23# P110 HC TMK UP SF Torq (spec sheet attached) from 11,605? to 22,743? Cement in one stage to surface Lead: 550 sx of 35:36:6 Class C (12.7 ppg / 1.98 cuft/ sx) Tail: 2700 sx of 50:50:2 Class H Blend (14.4 ppg / 1.25 cuft/sx)

Revisions to Operator-Submitted EC Data for Sundry Notice #462180

•

	Operator Submitted	BLM Revised (AFMSS)
Sundry Type:	APDCH NOI	APDCH NOI
Lease:	NMNM123532	NMNM123532
Agreement:		
Operator:	COG OPERATING LLC 2208 WEST MAIN STREET ARTESIA, NM 88210 Ph: 575-748-6940	COG OPERATING LLC ONE CONCHO CENTER 600 W ILLINOIS AVENUE MIDLAND, TX 79701-4287 Ph: 432.685.4342
Admin Contact:	MAYTE X REYES SENIOR REGULATORY ANALYST E-Mail: mreyes1@concho.com	MAYTE X REYES REGULATORY ANALYST E-Mail: mreyes1@concho.com
	Ph: 575-748-6945	Ph: 575-748-6945
Tech Contact:	MAYTE X REYES SENIOR REGULATORY ANALYST E-Mail: mreyes1@concho.com	MAYTE X REYES REGULATORY ANALYST E-Mail: mreyes1@concho.com
	Ph: 575-748-6945	Ph: 575-748-6945
Location: State: County:	NM LEA	NM LEA
Field/Pool:	WILDCAT; BONE SPRING	WILDCAT BONE SPRING
Well/Facility:	BASEBALL CAP FEDERAL COM 607H Sec 25 T24S R34E SWSW 340FSL 1030FWL	BASEBALL CAP FEDERAL COM 607H Sec 25 T24S R34E SWSW 340FSL 1030FWL 32.182133 N Lat, 103.428909 W Lon