Submit 1 Copy To Appropriate District Office		State of New Mexico		Form C-103	
<u>District 1</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240		Energy, Minerals and Natural Resources		Revised July 18, 2013 WELL API NO.	
<u>District II</u> – (575) 748-1283		OIL CONSERVATION DIVISION			6383
811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178		1220 South St. Francis Dr.			Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460	)	Santa Fe, NM 87505			FEE
1220 S. St. Francis Dr., Santa Fe, NM	-				13191
87505 SUNDRY NOTICES AND REPORTS ON WELLS				7. Lease Name or U	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH					
PROPOSALS.)				8. Well Number	
1. Type of Well: Oil Well 🖾 Gas Well 🗌 Other				10011	
2. Name of Operator EOG RESOURCES				9. OGRID Number 7377	
3. Address of Operator				10. Pool name or Wildcat	
P O BOX 2267, MIDLAND TX 79702				97838 JENNINGS; UPP	ER BONE SPRING SHALE
4. Well Location Unit Letter C :248 feet from the NORTH line and 1949 feet from the WEST line					
Unit Letter C		t from the NORT	$\frac{\text{H}}{\text{line and }} \frac{194}{225}$		
Section 36			ange 32E		ounty LEA CO,NM
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3400 gl					
12. Chec	k Appropriate 1	Box to Indicate N	Nature of Notice,	Report or Other Da	ita .
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING					
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS.					
PULL OR ALTER CASING DIMULTIPLE COMPL CASING/CEMENT JOB S DOWNHOLE COMMINGLE					
OTHER:			OTHER: DRIL	L CSG	Z
13. Describe proposed or co					
of starting any proposed proposed completion or		LE 19.15.7.14 NMA	C. For Multiple Col	npletions: Attach well	bore diagram of
		· •			
20" CONDUCTOR @ 115' 10/22/19 17-1/2" HOLE					
10/22/19 Surface Hole @ 895' MD, 894' TVD / Casing shoe @ 877' MD					
Ran 13-3/8" 54.5# J-55 STC Lead Cement w/ 580 sx Class C  (1.76 yld, 13.5 ppg), Trail w/200 sx Class C (1.36 yld, 14.8 ppg)					
Test casing to 1,500 psi for 30 min -OK. Circ 367 sx cement to surface Resume Drilling 12-1/2" hole					
		_			
Snud Data	·	Rig Release D	ato:		
Spud Date: 10/21/19		Rig Release D	ale.		
	<u></u>				
I hereby certify that the information	on above is true/a	nd complete to the b	est of my knowledge	e and belief.	
	n  /				
SIGNATURE MULTURE TITLE Sr. Regulatory Administrator DATE 10/28/19					
Type or print name Excitly Follis E-mail address: emily_follis@eogresources.comONE: 432-848-9163					
For State Use Only					
APPROVED BY:					
Conditions of Approval (if any):	$\mathcal{O}$			and the second	/