Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					Explics, Ja	inuary 31, 2016
					5. Lease Serial No. NMNM122619	
					6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No.	
Type of Well Gas Well □ Other					8. Well Name and No. DAUNTLESS 7 FED 709H	
Name of Operator					9. API Well No. 30-025-45598-00-X1	
3a. Address		(include area code) 10. Field and Pool or Exploratory Area				
PO BOX 2267 MIDLAND, TX 79702	Ph: 432-636-3600			RED HILLS		
4. Location of Well (Footage, Sec., 7	11. County or Parish, Sta			State		
Sec 7 T25S R33E SESW 349 32.138821 N Lat, 103.611458	LEA COUNTY, NM			NM		
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICAT	E NATURE O	F NOTICE,	REPORT, OR OTH	IER DATA
TYPE OF SUBMISSION	TYPE OF ACTION					
S Notice of Intent	☐ Acidize	☐ Deepe	en	☐ Production (Start/Resume)		☐ Water Shut-Off
□ Notice of Intent	☐ Alter Casing	☐ Hydra	ulic Fracturing	☐ Reclamation		■ Well Integrity
Subsequent Report	□ Casing Repair	□ New (Construction	□ Recomp	olete	Other
☐ Final Abandonment Notice	☐ Change Plans	Plug a	and Abandon	□ Temporarily Abandon		Drilling Operations
	☐ Convert to Injection	Plug l	Back	☐ Water Disposal		
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true 'vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection. 12/12/19 20" Conductor @ 115' 12/12/19 12-114" HOLE 12/25/19 Surface Hole @ 1,194' MD, 1,194' TVD Casing shoe @ 1,174' MD Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 540 sx Class C(1.64 yld, 13.8 ppg), Trail w/ 90 sx Class C (1.36 yld, 14.8 ppg) ' Test casing to 1,500 psi for 30 min - Good. Circ 298 sx cement to surface 12/30/19 8-3/4" hole 12/30/19 8-3/4" hole 12/30/19 Intermediate Hole @ 11,779' MD, 11,761' TVD Casing shoe @ 11,759' MD 14. I hereby certify that the foregoing is true and correct. Electronic Submission #498898 verified by the BLM Well Information System For EOG RESOURCES INCORPORATED, sent to the Hobbs Committed to AFMSS for processing by PRISCILLA PEREZ on 01/13/32020 (20PP0946SE)						
Name (Printed/Typed) EMILY FC	Title SR REGULATORY ADMINISTRATOR					
Signature (Electronic S	ubmission) Date 01/13/2020				<u></u>	<u> </u>
	THIS SPACE FO	OR FEDERAL	OR STATE	OFFICE U	SE	
Approved By ACCEPTED			JONATHON SHEPARD TitlePETROELUM ENGINEER Date 01/15/2020			
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduct the applicant the	Office Hobbs					
Title 18 LLS C. Section 1001 and Title 43 LLS C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United						

Fitle 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



Additional data for EC transaction #498898 that would not fit on the form

32. Additional remarks, continued

Ran 7-5/8", 29.7#, HCP-110 BTC SCC (0' - 1,019')
Ran 7-5/8", 29.7#, ECP-110 MO-FXL (1,019' - 11,759')
Stage 1: Lead Cement w/ 460 sx Class H(1.20 yld, 15.6 ppg)
Test casing to 2,600 psi for 30 min - good Did not circ cement to surface, TOC @ 7,072' by Calc Stage 2: Bradenhead squeeze w/ 1,000 sx Class C(1.5 yld, 14.8 ppg)
Stage 3: Top out w/ 45 sx Class C (1.50 yld, 14.8 ppg) Resume drilling 6-3/4" hole