Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					Lease Serial No. NMNM108504 If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No.	
Type of Well ☐ Gas Well ☐ Other					8. Well Name and No. JAVELINA 30 FED 703H	
Name of Operator					9. API Well No. 30-025-46559-00-X1	
3a. Address PO BOX 2267 MIDLAND, TX 79702	3b. Phone No. (include area code) Ph: 432-636-3600			10. Field and Pool or Exploratory Area BOBCAT DRAW-UPR WOLFCAMP		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, State	
Sec 30 T25S R34E SENW 22 32.102551 N Lat, 103.511086	LEA COUNTY			NM		
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE O	F NOTICE,	REPORT, OR OTH	IER DATA
TYPE OF SUBMISSION	TYPE OF ACTION					
□ Notice of Intent	☐ Acidize	☐ Dee	pen	☐ Production (Start/Resume)		■ Water Shut-Off
	☐ Alter Casing	□ Нус	raulic Fracturing	☐ Reclamation		■ Well Integrity
Subsequent Report	□ Casing Repair	ing Repair		☐ Recomplete		⊠ Other
☐ Final Abandonment Notice	☐ Change Plans	Plug and Abandon		☐ Temporarily Abandon Dr		Drilling Operations
	Convert to Injection	Plug Back		■ Water Disposal		
If the proposal is to deepen directions Attach the Bond under which the won following completion of the involved testing has been completed. Final At determined that the site is ready for final 12/10/19 20" Conductor @ 17/12/26/19 12-1/4" HOLE 12/26/19 Surface Hole @ 1,15 Casing shoe @ 1,129' MD Ran 9-5/8" 40# J-55 LTC Lead Cement w/ 540 sx Class Test casing to 1,500 psi for 30/12/31/19 8-3/4" hole 12/31/19 Intermediate Hole @ Casing shoe @ 11,937' MD	k will be performed or provide operations. If the operation re anadonment Notices must be fil inal inspection. 15' 60' MD, 1,150' TVD C(1.64 yld, 13.8 ppg), Tra min - Good. Circ 257 sx	the Bond No. or sults in a multipled only after all	n file with BLM/BIA e completion or reco requirements, includ	. Required sub impletion in a r ing reclamation	sequent reports must be new interval, a Form 316 n. have been completed a	filed within 30 days 0-4 must be filed once
Com	# Electronic Submission For EOG RESOL nmitted to AFMSS for proc	IRCES INCOR	PORATED, sent t SCILLA PEREZ or	to the Hobbs 1 01/13/2020	(20PP0911SE)	
Name (Printed/Typed) EMILY FOLLIS			Title SR REGULATORY ADMINISTRATOR			
Signature (Electronic S	Submission)		Date 01/08/20	020		
	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE US	SE	
_Approved By ACCEPTED				JONATHON SHEPARD itlePETROELUM ENGINEER Date 01/		Date 01/15/2020
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conduct the conductive transfer of the conductive transfer or the conductive transfer of the conductive transfer or the conductive tran	Office Hobbs					
Title 18 U.S.C. Section 1001 and Title 43				willfully to ma	ke to any department or	agency of the United



Additional data for EC transaction #498399 that would not fit on the form

32. Additional remarks, continued

Ran 7-5/8", 29.7#, ECP-110 BTC SCC (0' - 1,531')
Ran 7-5/8", 29.7#, HCP-110 MO-FXL (1,531' - 11,937')
Stage 1: Lead Cement w/ 415 sx Class H(1.20 yld, 15.6 ppg)
Test casing to 2,700 psi for 30 min - Good Did not circ cement to surface, TOC @ 7,000' by Calc Stage 2: Bradenhead squeeze w/ 1,000 sx Class C(1.51 yld, 14.8 ppg)
Stage 3: Top out w/ 60 sx Class C (1.51 yld, 14.8 ppg) TOC @ surface Resume drilling 6-3/4"hole