

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DISTRICT
1220 South St. Francis Dr.
Santa Fe, NM 87505

HOBBS OGD
MAR 02 2020
RECEIVED

WELL API NO. 30-025-44467
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 313956
7. Lease Name or Unit Agreement Name NEPTUNE 10 STATE COM
8. Well Number #401H
9. OGRID Number 7377
10. Pool name or Wildcat 59900 TRIPLE X; BONE SPRING

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
EOG RESOURCES

3. Address of Operator
P O BOX 2267, MIDLAND TX 79702

4. Well Location
Unit Letter O : 163 feet from the SOUTH line and 2202 feet from the EAST line
Section 10 Township 24S Range 33E NMPM County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3613 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: DRILL CSG ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02/21/2020 12-1/4" hole
02/21/2020 1st Intermediate Hole @ 5,185' MD, 5,184' TVD
Casing shoe @ 5,170' MD
Ran 9-5/8", 40#, J-55 LTC (0' - 3,915')
Ran 9-5/8", 40#, HCK-55 LTC (3,915' - 5,170')
Lead Cement w/ 1,015 sx Class C (2.32 yld, 12.7 ppg), Trail w/ 415 sx Class C (1.42 yld, 14.8 ppg)
Test casing to 1,500 psi for 30 min - OK. Circ 312 sx cement to surface. Resume drilling 8-3/4" hole

J.P.M.

Spud Date:

02/07/2020

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Emily Folles TITLE Sr. Regulatory Administrator DATE 02/26/2020

Type or print name Emily Folles E-mail address: emily_folles@eogresources.com PHONE: 432-848-9163
For State Use Only

APPROVED BY: [Signature] TITLE DATE 03/05/2020
Conditions of Approval (if any):