

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

January 18, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

~~Amerada Petroleum Corporation~~ (Company or Operator) ~~W. F. Mathers~~ Well No. ~~1~~ in ~~11~~ (Unit)
~~SE~~ 1/4 ~~NE~~ 1/4 of Sec. ~~3~~, T. ~~12-S~~, R. ~~33-E~~ NMPM., ~~Bagley Siluro-Devonian~~ Pool
~~Lea~~ County.


FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Plan to pull 2-3/8" OD tubing and Kobe pumping equipment. Run 2-3/8" OD tubing and 4-3/4" bit. Drill out Baker Model "D" production packer at 9895'. Run retrievable cement retainer and set at approx. 10,913'. Squeeze present Devonian 5-1/2" casing perforations from 10,864' to 10,874', 10,880 to 10,910', 10,920' to 10,934' and open hole from 10,934' to 10,964' with 150 sacks S10-set cement. Drill out to 10,912' and perforate 5-1/2" OD casing with 2 bullet shots per foot from 10,866' to 10,872' by Micro log. Acidize with 500 gals. 15% regular acid. Swab test and rerun Kobe pump. Resume production.

Approved....., 19.....
Except as follows:

~~Amerada Petroleum Corporation~~
By ~~W. F. Mathers~~

Position..... ~~District Superintendent~~
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION
By 
Title.....

Name..... ~~Amerada Petroleum Corporation~~
Address..... ~~P.O. Box 668 Hobbs, New Mexico~~