

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

HOBBS OFFICE OCC

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)February 16, 1959
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Sinclair Oil & Gas Company State **Lea** **840** Well No. **1** in **N**
(Company or Operator) (Unit)
SW $\frac{1}{4}$ **SW** $\frac{1}{4}$ of Sec. **1**, T. **11**, R. **34**, NMPM, **Sand Springs Devonian** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 11745PB Atoka (NOTE: Offset operators have been notified of this intention
13-3/8" OD Csg set at 304' w/350 sacks cement.
9-5/8" OD Csg set at 4135' w/1700 sacks cement. in compliance w/Rule 201, NMCCC.)
5-1/2" OD Csg set at 13205' w/200 sacks cement.
Perforated 11601-11609 (Atoka).

PROPOSE TO: Plug and abandon well as follows: Fill hole w/heavy mud and then:
Spot 25 sack cement plug from 11415-11640.
Run Magnetometer and jet cut 5-1/2" Csg at approximately 11140' - and pull
5-1/2" OD Csg.
Spot 25 sack cement plug from 11100 to 11207.
Spot 40 sack cement plug from 9844-9950.
Spot 25 sack cement plug from 4100-4168.
Spot 15 sack cement plug in bottom of cellar & top of 13-3/8" Csg w/4"
regulation marker extending 4' above surface level.
Fill cellar, clean and level location.

Approved....., 19.....
Except as follows:**Sinclair Oil & Gas Company**
Company or Operator

By.....

Position..... **Dist. Supt.**

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSIONBy..... **John W. Runyan**

Title.....

Name..... **C.C. Salter**Address..... **520 E Broadway, Hobbs, N.M.**

Orig & 2cc: OCC; cc:FHR, HFD, File