

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- TA Gas Well	7. Unit Agreement Name
2. Name of Operator Sunray DX Oil Company	8. Farm or Lease Name U.D. Sawyer
3. Address of Operator Bx 128, Hobbs, New Mexico	9. Well No. 1
4. Location of Well UNIT LETTER 0 , 660 FEET FROM THE South LINE AND 1980' FEET FROM THE West LINE, SECTION 27 TOWNSHIP 9 RANGE 36 N.M.P.M.	10. Field and Pool, or Wildcat Crossroads
15. Elevation (Show whether DF, RT, GR, etc.) 4034 DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER PA in Devonian & Recomplete in San Andres <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- P&A Devonian as follows: Squeeze perms 12,100-12,182 w/50 sx cmt to 3500 psig. Top of cmt. in csg. 10,783' by wire line measurement.
- Perf 4949-50 w/4 "E" bullets, set cmt retainer @ 4920'. Circulate 105 sx Incore Pps behind csg. TOC 4570' by Temp. Survey.
- Perf 4851-52 & block squeeze w/100 sx cmt. Perf 4818-19 & block squeeze w/100 sx cmt. WOC.
- Drill cmt to 4852' & test squeeze 4851-52 & 4818-19 to 1,000# O.K.
- Perf San Andres 4820-25, 4827-30, 4832-35, 4846-50 w/2 bullets /ft. Acidize w/2,000 gal BDA. Frac w/776 bbl ref. oil & 20,000# sand.
- Recovered 649 BLO in 22 days. w/approx 700 MCF Gas per day. Well loaded up w/wtr & died. Could not swab off wtr. Well now T.A.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John Hastings **John Hastings** TITLE Production Engineer DATE 2-3-65

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: