

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O.C.C.

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 5 8 59 AM '67

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name Flying M (SA) Unit
2. Name of Operator Coastal States Gas Producing Company	8. Farm or Lease Name Flying M (SA) Un. Tr. 22
3. Address of Operator P. O. Box 235, Midland, Texas 79701	9. Well No. 4
4. Location of Well UNIT LETTER N , 849.6 FEET FROM THE south LINE AND 1987.4 FEET FROM west 28 9S 33E THE west LINE, SECTION 28 TOWNSHIP 9S RANGE 33E NMPM.	10. Field and Pool, or Wildcat Flying M (SA)
15. Elevation (Show whether DF, RT, GR, etc.) 4317.2'	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

XPUD DATE: 8 p.m. 6-19-67

6-30-67: Ran 143 jts, 4-1/2" OD, 9.5#, J-55, Cond B casing with guide shoe at 4573' and float collar at 4540'. Cemented with 450 gals chemical wash, 250 sx Cl "C", 50-50 Litepoz, 4% gel and 27 sx Cl "C" with 300 gallons Cealment. Bumped plug with 1000 psi, held OK. PD at 6 p.m. 6-29-67. WOC 14 hours.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Div. Prod. Supt. DATE July 3, 1967

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: