

(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R142

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 067081

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

INSALL FEDERAL COM

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

VADA BOUGH C

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

12-9S-34E

12. COUNTY OR PARISH

LEA

13. STATE

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ JUN 11 11 41 AM '68

2. NAME OF OPERATOR

TENNECO OIL COMPANY

3. ADDRESS OF OPERATOR

Box 1031 MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' ESL: 660' FWL, UNIT M, SEC 12, T9S, R34E, NM PM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4226 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SPUD 4-28-68 4:00PM

DRILLED 17 1/2 HOLE TO 366'

RAN 11 JTS 13 3/8 48# H-40 STC CASING SET AT 364'

CEMENTED CASING WITH 225 SX CLASS C POZ MIX WITH 2%

CACl₂, 2% GEL WITH 1/4# / SX FLOCELE AND 100 SX CLASS

C CEMENT WITH 2% CACl₂. CEMENT CIRCULATED. PD 5:30 AM

WOL 22 HRS. TESTED CASING TO 800# FOR 30 MINUTES -

HELD OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

Monroe K. Karasch

TITLE

SR. PROD. CLERK

DATE

6-7-68

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

JUN 10 1968

*See Instructions on Reverse Side J L GORDON
ACTING DISTRICT ENGINEER