

CONSERVATION DIVISION

P. O. BOX 2038
SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-73

WELL NO.	
DATE COMPLETED	
WELL TYPE	
WELL STATUS	
WELL DEPTH	
WELL LOCATION	
WELL OWNER	

5a. Indicate Type of Lease
State ☐ For ☒

5b. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR LADDER, LIFT, OR TO OTHER PURPOSES (IT IS A DIFFERENT RESERVOIR, USE APPLICATION FOR LADDER - 101 (FORM C-101) FOR SUCH PURPOSES.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

The Superior Oil Company

Address of Operator

P. O. Box 71, Conroe, Texas 77301

Location of Well

UNIT LETTER L 1830 FEET FROM THE South LINE AND 660 FEET FROM
THE West LINE, SECTION 22 TOWNSHIP 9-S RANGE 34-E NEARBY

7. Unit Agreement Date

8. Party or Lease Name

Pruitt Com.

9. Well No.

1

10. Field and Pool, or Wildcat

Wolfcamp

11. Elevation (show whether DF, RT, GR, etc.)

GL 4233 KB 4248

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
FULL OR ALTER CASING ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPER. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Recommended Procedure:

1. Load well w/wtr, install BOP, pull rods & pump. & pull tubing.
2. Set a 100' balanced cement plug (45 sxs) from 9400' to 9500'. and tag top of plug.
3. Fill hole w/10#/gal saltwater gel mud & POH.
4. Determine freepoint on 5 1/2" csg & cut csg at freepoint & POH.
5. Set 100' cement plug 50' in & 50' out 5 1/2" csg stub w/45 sxs cement, tag top.
6. Set 100' cement plug from 7682' to 7782' & from 5405-5505 using 45 sxs each plug.
7. Set 100' cement plug in 8-5/8" csg at top of Salido Formation 440-540 w/45 sxs cement. Dump 10' of cement in top of 8-5/8" csg.
8. Mark well in accordance w/NM Oil Conservation Commission.

NOTIFY COMMISSION 24 HRS PRIOR TO SETTING FIRST PLUG

100' PLUG - 4250 - 4150
100' PLUG - 440-540 MUST BE PLACED BOTH INSIDE
& OUT SIDE - 8 1/8"

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED G. Bannantine G. Bannantine TITLE Regulatory Group Manager DATE 2-11-80

APPROVED BY [Signature] CONDITIONS OF APPROVAL, IF ANY:

TITLE SUPERVISOR DISTRICT

DATE FEB 22 1980