

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 1650	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 1715	T. Strawn 10,016	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2435	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3730	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta 5115	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinberry	T. Gr. Wash	T. Morrison	T.
T. Tubb 6500	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo 7226	T. Bone Springs	T. Wingate	T.
T. Wolfcamp 8545	T. Middle Penn 9874	T. Chinle	T.
T. Penn.	T.	T. Permian	T.
T. Cisco (Bough C) 9096	T.	T. Penn. "A"	T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	360	360	Surface Sands				
360	1650	1290	Red Bed				
1650	2435	785	Anhydrite & Salt				
2435	2560	125	Lime & Sand				
2560	3730	1170	Lime & Anhydrite				
3730	5115	1385	Lime & Dolomite				
5115	6500	1385	Dolomite & Sand				
6500	7225	725	Dolomite, Shale & Sand				
7225	7590	1125	Lime & Shale				
7590	8350	760	Lime & Dolomite				
8350	10350	2000	Lime & Shale				