

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Drilling Well	7. Unit Agreement Name
2. Name of Operator Southern Minerals Corporation	8. Farm or Lease Name State "D"
3. Address of Operator P. O. Box 716 - Corpus Christi, Texas 78403	9. Well No. 4
4. Location of Well UNIT LETTER G , 1980 FEET FROM THE East LINE AND 1830 FEET FROM THE North LINE, SECTION 8 TOWNSHIP 11-S RANGE 34-E NMPM.	10. Field and Pool, or Wildcat Inbe Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4200.9 G.L.	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 7:00 P.M., February 4, 1969. Drilled 17 1/2" hole to 385'. Ran 12 joints of 13 3/8", 48#, H-40 casing. Casing set at 381". Cemented with 375 sacks Class H Cement plus 2% Calcium Chloride. Plug down 12:00 Noon, Feb. 5, 1969. Had cement returns to surface. Waited 18 hrs. on cement and tested casing to 1,000#, held O.K..

February 10, 1969, drilled 12 1/4" hole to 4045'. Ran 129 joints of 9 5/8", 36# & 32.3#, J-55 & H-40 casing set at 4045'. Cemented with 400 sacks of Incor Neat Cement followed with 150 sacks of Incor plus 2% Calcium Chloride. Plug down 5:00 P.M., Feb. 10, 1969. Waited 18 hrs. on cement and tested to 1700#, held O.K..

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. K. Heinrich TITLE Authorized Employee DATE February 12, 1969

APPROVED BY [Signature] TITLE SUPERVISOR DISTRICT 1 DATE

CONDITIONS OF APPROVAL, IF ANY: