

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN THE ORIGINAL  
(Other instructions on  
reverse side)

Form Approved  
Budget Bureau No. 42-11424  
6. LEASE DENIGATION AND SERIAL

N1110554 779  
6. IF INDIAN, ALLOTTED OR TRUST

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL  GAS WELL  OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR  
Humble Oil & Refining Co.

8. FARM OR LEASE NAME  
Andrews Fed.

3. ADDRESS OF OPERATOR  
% Hobbs Pipe & Supply Co, Box 2010, Hobbs, N.M.

9. WELL NO.  
1

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

10. FIELD AND POOL, OR WILDCAT  
Chaveroo San Andres

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)  
4444 DF

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA  
S30-T7S-R33E

12. COUNTY OR PARISH  
Roosevelt

13. STATE  
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF   
FRACTURE TREAT   
SHOOT OR ACIDIZE   
REPAIR WELL   
(Other)   
FULL OR ALTER CASING   
MULTIPLE COMPLETE   
ABANDON\*   
CHANGE PLANS

WATER SHUT-OFF   
FRACTURE TREATMENT   
SHOOTING OR ACIDIZING   
(Other)   
REPAIRING WELL   
ALTERING CASING   
ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Spotted a 35 sack cement plug on bottom at 4364'.
2. Spotted a 25 sack cement plug at 4 1/2" casing stub at 1295'.
3. Spotted a 25 sack cement plug at 8 5/8" casing shoe at 220'.
4. Spotted a 10 sack cement plug at surface with marker.
5. Hole was loaded with mud laden fluids.

RECEIVED  
OCT 29 1970  
CENTRAL FILE ROOM

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Agent

DATE 12-23-69

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_  
APPROVED \_\_\_\_\_ DATE \_\_\_\_\_

OCT 2 1970

\*See Instructions on Reverse Side

J L GORDON  
ACTING DISTRICT ENGINEER