

UNITED STATES N. M. OIL & GAS COMM. IN  
DEPARTMENT OF THE INTERIOR (Other Instructions on re-  
v. 10-1-80)  
BUREAU OF LAND MANAGEMENT ROSWELL, NEW MEXICO 88240

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.  
NM-0608-TUP-74 (NM-8143)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Cato Sub

9. WELL NO.  
5-D

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR B.L.K. AND SURVEY OR AREA

Sec 5, T-8S, R-30E

1. OIL WELL  GAS WELL  OTHER Salt Water Disposal

2. NAME OF OPERATOR  
MWJ PRODUCING COMPANY

3. ADDRESS OF OPERATOR  
400 W. Illinois - Suite 1100 Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface.

660' FSL & 660' FEL Section 5, T-8S, R-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4030' GL

12. COUNTY OR PARISH

Chaves

18. STATE

New Mexico

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugging Instructions as per Pete Chester 1/26/90:

1. Cement plug from 7960-7780' (tag).
2. Cement plug from 4341-4191' (tag).
3. Cement plug from 2041-1921'
4. Cement plug from 788-688'.
5. Cement plug from 50' to surface (minimum).
6. Install dry hole marker.

NOTE: Mud between plugs 25# saltgel per bbl of wtr.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Pat Drexler*

TITLE Pat Drexler-Agent

DATE 1/29/90

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

SUBJECT TO LIKE APPROVAL BY STATE

DATE

APPROVED

PETER W. CHESTER

FEB 1 1990

\*See Instructions on Reverse Side

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA