

ED 4471 DF

COUNTY CHAVES FIELD Chaverco STATE NM  
 OPR CHAMPLIN PETROLEUM COMPANY MAP  
 3 State "6"  
 Sec. 6, T-8-S, R-33-E CO-ORD  
 660' FNL, 1980' FWL of Sec. MC 10456  
 Spd 6-4-66 CLASS EL [REDACTED]  
 Cmp 6-30-66

| CSG & SX - TUBING      | FORMATION |       | DATUM     |       |
|------------------------|-----------|-------|-----------|-------|
|                        | FORMATION | DATUM | FORMATION | DATUM |
| 8 5/8" 364' 200        |           |       |           |       |
| 4 1/2" 4415' 325       |           |       |           |       |
|                        |           |       |           |       |
|                        |           |       |           |       |
|                        |           |       |           |       |
|                        |           |       |           |       |
| LOGS EL GR RA IND HC A |           |       |           |       |

TD 4415', PED 4413'  
 IP San Andres Perfs 4162-4330' Pmpd 52 BOPD + 78 BW. Pot. Based on 24 hr test, gravity 25.

Distribution limited and publication prohibited by subscribers' agreement.  
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton PROP DEPTH 4500' TYPE  
 DATE

F.R. 6-2-66  
 PD 4500' - SA  
 Contractor - Sitton & Norton  
 6-6-66 Prep to Spud  
 6-13-66 Drig. 3890' lm.  
 6-20-66 TD 4339', fishing.  
 6-27-66 TD 4415', PED 4413', prep to perf.  
 7-5-66 TD 4415', PED 4413', tstg on pump.  
 Perf @ 4162', 4191', 4200', 4221',  
 4240', 4245', 4290', 4300', 4308',  
 4330' W/2 SPI  
 Ac (4162-4330') 500 gals.  
 Frac (4162-4330') 50,000 gals wtr +  
 40,000# sd.  
 Pmpd 130 BF (90% LW - 10% oil) in 24 hrs.  
 7-11-66 TD 4415', PED 4413', COMPLETED.  
 LCG TOPS: Anhydrite 1830', Yates 2319',  
 Queen 2992', San Andres 3560'.