

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLIC.  
(Other instructions on  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0354478

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

1.

OIL WELL  GAS WELL  OTHER Wildcat

2. NAME OF OPERATOR

Grover, MacCurdy and Hoffacker

3. ADDRESS OF OPERATOR

306 Midland Nat'l Bank Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660' FSL and 660' FWL of Section 19

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shell-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLEK. AND SURVEY OR AREA

Sec 19, T9S, R30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4039.9 Gr

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3/29 Spotted 15 sx cement plug thru tubing from 3365' to 3181'. (184')  
Cut off 4 1/2" casing @ 2310' w/Perfo jet casing cutter & pulled 4 1/2" casing out of hole.  
Spotted the following cement plugs:  
40 sx - 2360 to 2209' (157')  
40 sx - 1449 to 1331' (118')  
40 sx - 408' to 293' (115')  
10 sx - 22' to surface (22') - heavy mud placed between cement plugs.

P&A @ 6 PM 3/29/68 with a 4 1/2" OD Pipe Marker cemented in top of 8 5/8" OD casing, extending 4' above surface w/name and location on marker.  
No 8 5/8" casing pulled. Well site conditioned and ready for final inspection on 5/1/68.

18. I hereby certify that the foregoing is true and correct.

SIGNED

*Wildcat R MacCurdy*

TITLE

Partner

DATE

4-8-68

(This space for Federal or State office use)

RECEIVED

APPROVED BY

TITLE

DATE

APR 10 1968

CONDITIONS OF APPROVAL, IF ANY:

SEP 18 1968

J. W. SUTHERLAND  
DISTRICT ENGINEER

\*See Instructions on Reverse Side