

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. Federal NM 055564	
2. NAME OF OPERATOR Humble Oil & Refining Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Box 1600, Midland, Texas 79701		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1,980' FSL & 660' FEL		8. FARM OR LEASE NAME Isler-Federal	
14. PERMIT NO.		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4,014 GR 4,027 DF		10. FIELD AND POOL, OR WILDCAT Many Gates - Abo	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 31, T-9-S, R-30-E	
		12. COUNTY OR PARISH Chaves	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to depth of 7,330'.

Plug No.	Sacks	Type	Plug From	To
1	35	Class "H"	7,250	7,150
2	40	Class "H"	3,998	3,898
3	40	Class "H"	3,300	3,200
4	40	Class "H"	2,180	2,080
5	35	Class "H"	1,547	1,447
6	10	Class "H"	34	4

4' below ground level. Cleaned pit; installed dry hole marker, released rig at 7:00 a.m. 10-21-72. Welded plate on surface casing with 1", 1000 psi WP valve. Placed 10.3% mud laden fluid between plugs. No casing was plugged.

Verbal approval received from NMOCC prior to actual P&A.

RECEIVED
OCT 26 1972
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Unit Head DATE October 24, 1972

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
MAY 3 - 1973
H. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side