

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-3351

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Champlin Petroleum Company 3. Address of Operator 300 Wilco Building Midland, Texas 79701 4. Location of Well UNIT LETTER G, 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 5 TOWNSHIP 8-S RANGE 33-E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 4435 GR	7. Unit Agreement Name 8. Farm or Lease Name State 5-8-33 9. Well No. 5 10. Field and Pool, or Wildcat Chaveroo-San Andres 12. County Chaves
---	--

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Sitton Drilling Company spudded 5:45 P. M. 8-25-76. Drilled 12-1/4" hole, 1150, 11" hole to 1940'. Set 8-5/8" 24# @ 1938' and cemented w/650 sacks Litegate followed by 200 sacks Class "C" w/2% CaCl. Plug down 12:00 P.M. W.O.C. 18 hrs. Tested BOP and casing to 800# for 30 Min. Tested OK. Drilled 7-7/8" hole to 4525', set 4-1/2 10.50# @ 4525' and cemented w/250 sacks 50-50 pozmix w/2% gel & 8# salt/sack. Plug down 2:15 P.M. 9-2-76. W.O.C. 137 hrs. Tested casing to 1000# for 30 min. Tested OK. Perforated San Andres 4223, 4227, 4242, 4244, 4247, 4249, 4270, 4273, 4276, 4316, 4319, 4322, 4325, 4335, 4338, 4341, 4344, 4352, 4366 & 4401. Treated perms 4223-4276 w/1500 gals. 15% HCL, treated perms 4316-4401 w/2500 gals. 15% HCL. Swabbed tested well. Fractured perms 4223-4401 w/50,000 gals. gelled KCL water & 70,000# 20-40 sand. Swabbed tested well. Ran tubing & rods w/pump for completion.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Walter M. R. Delgado TITLE District Clerk DATE Sept. 21, 1976

Orig. Signed by  
Joni Sexton

APPROVED BY Dist. 1, Supv. TITLE \_\_\_\_\_ DATE SEP 23 1976

CONDITIONS OF APPROVAL, IF ANY: