



NEW MEXICO OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before beginning work. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		NOTICE OF INTENTION TO SET RETAINER AND PERFORATE CASING	X

Mussumut, New Mexico  
Place

July 11, 1951  
Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the

**Amurda Petroleum Corporation** State of **TX** Well No. **1** in **C/NE/4 NW/4**  
Company or Operator Lease  
of Sec. **26**, T. **12-S**, R. **12-E**, N. M. P. M., **Hightower** Field.  
**Lee** County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

11,199' - Total Depth, 10,165' Plugged Back Depth. On August 28 & 29, 1949, a Magnesium Retainer was set at 10,165' & the 5-1/2" casing perforations, from 10,170' to 10,180', were squeezed off with 100 sacks of cement and the casing was perforated from 10,165' to 10,155', 1/4 shots per foot, and acidized with 250 Gal. In 19-14 hrs. well flowed 788.14 bbls. oil, no water, through a 1/4" choke, G.O.P. 306. On a production test in May, 1951, this well produced 215 bbls. oil & 289 bbls. water in 24 hrs., G.O.P. 596. On June 1, 1951, while flowing on an open 3/4" choke, the well died. After continuous snubbing of 90% salt water, from June 16 to 21, well would not kick off. In an attempt to shut off water we plan to set a Baker Model "T" Magnesium Retainer at 10,165' and squeeze 5-1/2" casing perforations from 10,155' to 10,165', with 100 sacks cement and perforate 5-1/2" casing from 10,180' to 10,195' with 4 Jet Shots per foot and attempt to bring the well in without use of chemicals.

Approved \_\_\_\_\_, 19\_\_\_\_  
except at follows: JUL 13 1951

**Amurda Petroleum Corporation**  
Company or Operator

By \_\_\_\_\_

Position **Assistant District Superintendent**

Send communications regarding well to

Name **Amurda Petroleum Corporation**

Address **Drawer B, Mussumut, New Mexico**

OIL CONSERVATION COMMISSION,

By **Ray Yachraugh**  
Title **Oil & Gas Inspector**

10/10/1914

10/10/1914

10/10/1914

10/10/1914

10/10/1914

10/10/1914

10/10/1914

10/10/1914

10/10/1914

10/10/1914

10/10/1914

10/10/1914