NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MOSOS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before 166 with specified is to bign. A Dapy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Notice of Intention to Change Plans		Notice of Intention to Temporarily Abandon V	VELL	Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well		Notice of Intention to Plug Back		Notice of Intention to Set Liner	
Notice of Intention to Squeeze		Notice of Intention to Acidize	x	Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	x	Notice of Intention (Other)		Notice of Intention (Other)	
OIL CONSERVATION		Lovington, New	· · · · · · · · · · · · · · · · · · ·	May 15, 19)6 1
		(Fine	e)	(Date)	
Gentlemen:					
•				•	
	Company or Operato		rakt	Well Noi	n(Unit)
SW SE	% of Sec. 33	14-S	33-E NMPN	Saunders	Pool
(40-acre Subdivisi	ion)				
10,020'	(FOLLOV ID Present DOD	LL DETAILS OF PROP V INSTRUCTIONS IN TH 10,000 - INTENSION	ie rules and NS: Pull 2-	REGULATIONS) -3/8" OD Tubing, Gas	Lift Valves,
10,020' ' & Product with 2 si 9930' to during a	FUI (FOLLOW) ID Present DOD tion Packer. I hots per foot. 9966' with 300 old treatment.	LL DETAILS OF PROP V INSTRUCTIONS IN TH 10,000° - INTENSIC Perforate 5-1/2° Ca Acidize New Perfo 00 Gallons 15% acid	NS: Pull 2- asing from Sorations as i and use re mr & holdde	REGULATIONS)	1031 to 99081 Pations from Jected constan
10,020' ' & Product with 2 si 9930' to during a	FUI (FOLLOW) ID Present DOD tion Packer. I hots per foot. 9966' with 300 old treatment.	LL DETAILS OF PROP V INSTRUCTIONS IN TH 10,000° - INTENSION Perforate 5-1/2° Con Acidize New Perform OG Gallons 15% acid Pull tubing, pack	NS: Pull 2- asing from Sorations as i and use re mr & holdde	REGULATIONS) -3/8" OD Tubing, Gas -859' to 9865' and 99 above and old perfor abber ball sealers in	1031 to 99081 Pations from Jected constan
10,020' ' & Product with 2 si 9930' to during a	FUI (FOLLOW) ID Present DOD tion Packer. I hots per foot. 9966' with 300 old treatment.	LL DETAILS OF PROP V INSTRUCTIONS IN TH 10,000° - INTENSION Perforate 5-1/2° Con Acidize New Perform OG Gallons 15% acid Pull tubing, pack	NS: Pull 2- asing from 9 orations as i and use re cer & holdde	REGULATIONS) -3/8" OD Tubing, Gas -859' to 9865' and 99 above and old perfor abber ball sealers in own and rerun 2-3/8"	03! to 9908 [†] Pations from Ujected constan OD Tubing,
10,020' ' & Product with 2 st 9930' to during as gas lift	FUI (FOLLOW) ID Present DOD tion Packer. I hots per foot. 9966' with 300 old treatment.	LL DETAILS OF PROP V INSTRUCTIONS IN TH 10,000° - INTENSIC Perforate 5-1/2° Ca Acidize New Perfo CO Gallons 15% acid Pull tubing, pack and resume production	NS: Pull 2- asing from 9 orations as i and use re cer & holdde	REGULATIONS) -3/8" OD Tubing, Gas -859! to 9865! and 99 above and old perfor abber ball sealers in own and rerun 2-3/8"	03! to 9908 [†] Pations from Ujected constan OD Tubing,
10,020' ' & Product with 2 si 9930' to during ac gas lift	FUI (FOLLOW) TO Present DOD tion Packer. I nots per foot. 9966' with 300 old treatment. flow valves as	LL DETAILS OF PROP V INSTRUCTIONS IN TH 10,000 - INTENSIC Perforate 5-1/2" Ca Acidize New Perfo CO Gallons 15% acid Pull tubing, pack and resume production	NS: Pull 2- asing from 9 orations as i and use re cer & holdde	REGULATIONS) -3/8" OD Tubing, Gas -859' to 9865' and 99 above and old perfor abber ball sealers in own and rerun 2-3/8"	03! to 9908 [†] Pations from Ujected constan OD Tubing,
10,020' ' & Product with 2 st 9930' to during as gas lift	FUI (FOLLOW) TO Present DOD tion Packer. I nots per foot. 9966' with 300 old treatment. flow valves as	LL DETAILS OF PROP V INSTRUCTIONS IN THE 10,000° - INTENSIC Perforate 5-1/2° Ca Acidize New Perfo CO Gallons 15% acid Pull tubing, pack and resume production	Ampra	REGULATIONS) -3/8" OD Tubing, Gas -859' to 9865' and 99 above and old perfor abber ball sealers in own and rerun 2-3/8"	tion of the constant of the co
10,020' '& Product with 2 st 9930' to during as gas lift Approved	FUI (FOLLOW) TD Present DOD tion Packer. In ests per foot. 9966' with 300 cid treatment. flow valves an	LL DETAILS OF PROP V INSTRUCTIONS IN THE 10,000° - INTENSIC Perforate 5-1/2° Ca Acidize New Perfo CO Gallons 15% acid Pull tubing, pack and resume production	Ampre	REGULATIONS) -3/8" OD Tubing, Gas -859' to 9865' and 99 above and old perforabber ball sealers in own and rerun 2-3/8" Company or Operator	eations from jected constant OD Tubing,
10,020' '& Product with 2 st 9930' to during as gas lift Approved	FUI (FOLLOW) TD Present DOD tion Packer. In ests per foot. 9966' with 300 cid treatment. flow valves an	LL DETAILS OF PROP V INSTRUCTIONS IN TH 10,000' - INTENSIC Perforate 5-1/2" Ca Acidize New Perfo CO Gallons 15% acid Pull tubing, pack and resume production 19	Ampre	REGULATIONS) -3/8" OD Tubing, Gas -859' to 9865' and 99 above and old perforabler ball sealers in own and rerun 2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8" -2-3/8"	eations from jected constant OD Tubing, tion mtendent
10,020' '& Product with 2 st 9930' to during as gas lift Approved	FUI (FOLLOW) TD Present DOD tion Packer. In ests per foot. 9966' with 300 cid treatment. flow valves an	LL DETAILS OF PROP V INSTRUCTIONS IN TH 10,000' - INTENSIC Perforate 5-1/2" Ca Acidize New Perfo CO Gallons 15% acid Pull tubing, pack and resume production 19	Amera Amera Amera Amera Amera Amera	REGULATIONS) -3/8" OD Tubing, Gas -859! to 9865! and 99 above and old perfor abber ball sealers in own and rerun 2-3/8" Company or Operator stant District Superior d Communications regarding we	eations from jected constant OD Tubing, ution ntendent