| BE PROPOSED I | | | N OR PLUG BACK, GIVE : | | ODUCTIVE ZON | E AND PROPOSED NEW PRO |
|---------------------------|---|---|--|--|---|--|
| 8-9 | -68 | | | | | |
| < AZZZOVA FOR ON HA | VL 174 | | | Traffic Stephie | | |
| 5-1 | ./2 | 17 | 10300 | 600 | | 9000' |
| | | 24 , 32 | 4220 | | | 3500' |
| | | | | | - CEMENT | EST. TOP |
| SIZE | | | | | | |
| | | | | | | 14y - 2U, 1908 |
| ner DF, KT, etc.) | | | 21B. Drilling Contr | actor | 22. Appro | x. Date Work will start |
| | | | 10.300 | Pennov | | 20. Rotary or C.T. Rotary |
| | | | | | Lea | |
| FROM THE | East Line | OF SEC. 2 | TWP. 14-S RG | E. 33-E NMPM | 12. County | |
| LETTER G | LOCA | тер1980 | FEET FROM THE | | iiiii | |
| Southwes | t, Midland | , Texas 797 | 701 | | 10. Field o | and Pool, or Wildcat J Penn |
| | | | ZONE L | ZONE | 9. Well No | |
| OIL X GAS SINGLE MULTIPLE | | | | | 1 | Lease Name |
| _ | | | N, OR PLUG BAC | CK | 7. Unit Ag | reement Name |
| TATION FOR | DEDUIT TO | 2011 25505 | | | | K6231 |
| | | | | | L | X FEE 1 & Gas Lease No. |
| | | | | | | te Type of Lease |
| 1 1 1 | | | | | | - 65 |
| | Smith, Inc F Southwest T LETTER G ASSIZE C 13-3 8-5 5-1 | Smith, Inc. F Southwest, Midland T LETTER G LOCA THE FROM THE East LINE THE PROPOSED PROGRAM IS BE THE PROPOSED PROGRAM IS BE THE PROPOSED PROGRAM IS BE THE PROPOSED PROGRAM IS BE | DEEPEN DE DE DEEPEN DE DE DE DEEPEN DE DE DEEPEN DE DE DEEPEN DE DEEPEN DE DE DE DE DE DEEPEN DE DE DE DE DE | DEEPEN SINGLE SOUTHER STATE OF SEC. 2 TWP. 14-S REPORTED CASING WEIGHT PER FOOT SETTING DISTRIBUTION SETTING DISTR | SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF SEC. 13-3/8 44 32 4220 500 5-1/2 17 10300 600 | CATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK L X DEEPEN PLUG BACK SINGLE MULTIPLE HUBER Smith, Inc. F Southwest, Midland, Texas 79701 Lazy Lea Lea Located 19801 FEET FROM THE NOrth LINE LEAST LINE OF SEC. 2 TWP. 14-S ASE. 33-F NAMEN Lea Lea 10, 300 Pennsylvanian PROPOSED CASING AND CEMENT PROGRAM SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT 13-3/8 48 375 350 8-5/8 24, 32 4220 500 5-1/2 17 10300 600 |