U.S.G.S. LAND OFFICE OPERATOR SUNDRY NOTICES AND REPORTS ON WELLS From 15 SUNDRY NOTICES AND REPORTS ON WELLS ON NOTICE SAND REPORTS ON WELLS SET OF THE WELL SAND REPORTS ON WELLS ON NOTICE SAND REPORTS ON WELLS ON NOTICE SAND REPORTS ON WELLS SET OF THE WELL SAND REPORTS ON WELLS ON NOTICE SAND REPORTS ON WELLS SET OF THE WELL SAND REPORTS ON WELLS ON NOTICE SAND REPORTS OF THE WELL SAND REPORT	NO. OF COPIES RECEIVED DISTRIBUTION SANTA FE FILE	NEW MEXICO OIL CONS	ERVATION COMMISSION	Form C-103 Supersedes Old C-102 and C-103 Effective 1-1-65	
Solution of Well Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Notice of Intention to: Plug and Abandon Plug and Alferta (Abandon Plug and Alferta (Abandon) (Abandon Plug and Abandon Plug and Abandon Plug and Alferta (Abandon) (Abandon Plug and Abandon (Abandon) (Abandon Plug and Abandon Plug and Abandon Plug and Abandon Plug and Abandon (Abandon) (Abandon Plug and Abandon Plug and Abandon Plug and Abandon Plug and Abandon (Abandon) (Abandon Plug and Abandon Plug and Abandon Plug and Abandon Plug and Abandon (Abandon Plug and Abandon P				5a. Indicate Type of	Lease
S. Subtroot & Contense No. Content use this result and printing Sunday Notices and reports on Wells Sunday Notices S	<u> </u>			State ื	Fee
SUNDRY NOTICES AND REPORTS ON WELLS 1. 1. 1. 1. 1. 1. 1. 1				5. State Oil & Gas I	_ease No.
SUNDRY NOTICES AND REPORTS ON WELLS TO NOT USE THIS SOME YOUR SERVICES CARTEST OF THE PROPERTY POWER		L		K-3573	
OTHER WELL WELL OTHER. Drilling 2. Name of Operation 3. Address of Operation 3. Address of Operation 3. Address of Operation 4. Location of Well Unit LETTER B . 660 THE CAST V LINE, SECTION 19 TOWNSHIP 14-S RANGE 35-E HAMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 4074' DF 4057' GL Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PRAFORM REMEDIAL WORK TEMPORABLY ABARDON SULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1903. Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 14,787' csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sack plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	(DO NOT USE THIS FORM FO				
Amerada Hess Corporation 3. Address of Operator F. O. Box 1920 - Hobbs, New Mexico 88240 4. Location of Well UNIT LETER B	OIL GAS WELL	OTHER- Drilling			
3. Address of Operator P. O. Box 1920 - Hobbs, New Mexico 88240 4. Location of Well UNIT LETTER B . 660 FEET FROM THE NOTTH LINE AND 1980 FEET FROM THE NOTTH LINE AND 1980 FEET FROM Wildcat 15. Elevation (Show whether DF, RT, GR, etc.) Lea Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: FERFORM HEMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER Drilled to TD of 15,038', set 13-3/8" cag. at 384' with 400 sacks cement and 9-5/8" cag. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" cag. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" cag. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD cag. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" cag. for 41' and 10 sacks plug from 0 to 10' in top of 13-3/8" cag. with 4" x 6' dry hole marker. Completed as a					
P. O. Box 1920 - Hobbs, New Mexico 88240 1. A. Location of Well UNIT LETTER B 660 PEET FROM THE NOTTH LINE AND 1980 PEET FROM THE NOTTH LINE AND 1980 PEET FROM THE NOTTH LINE AND 1980 PEET FROM THE NOTTH 14-S RANGE 35-E NAMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 4074¹ DF 4057¹ GL Lea Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PULL OR ALTER CASING TEMPORABILLY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE ROLE 1103. Drilled to TD of 15,038¹, set 13-3/8" csg. at 384¹ with 400 sacks cement and 9-5/8" csg. at 4530¹ with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787¹ to 14,872¹, 10,419¹ to 10,504¹, 9605¹ to 9650¹. 25 sack cement plugs from 8070¹ to 8130¹, 5860¹ to 5950¹, in 9-5/8" csg. and 8-3/4" hole from 4502¹ to 4562¹. Shot 9-5/8" csg. off at 1095¹. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116¹. Spotted 25 sacks cement in 13-3/8" csg. with 4" x 6¹ dry hole marker. Completed as a					
UNIT LETTER B . 660 THE CAST V LINE, SECTION 19 TOWNSHIP 14-S RANGE 35-E HAPPM. 15. Elevation (Show whether DF, RT, GR, etc.) 4074' DF 4057' GL Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK COMMENCE DELILLING OPNS. CHANGE PLANS CHANGE DELILLING OPNS. CHANGE PLANS CHANGE DELILLING OPNS. CASING TEST AND CEMENT JGB OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sacks cement n 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sacks plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	P. O. Box 1920 -	Hobbs, New Mexico 88240		11	
THE PEAST V LINE, SECTION 19 TOWNSHIP 14-S RANGE 35-E NAMPOW. 15. Elevation (Show whether DF, RT, GR, etc.) 4074' DF 4057' GL Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE ORILLING OPNS. OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sacks cement in 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sack plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	1	660 FEET FROM THE NORth	1980 FEET	,	
The composed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. at 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" objected 25 sacks cement in 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	UNII LETTER,	FEET PROW THE			
The composed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. at 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" objected 25 sacks cement in 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	THE east V INE	19 TOWNSHIP 14-5	B RANGE 35-E	MPM (
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703. Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sacks plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	CINE,	TOWNS TO THE PARTY TOWNS TOWN TOWNS TO THE PARTY TOWN TOWN TOWN TOWN TOWN TOWN TO THE PARTY TOWN TOWN TOWN TOWN TOWN TOWN TOWN TOWN			
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sack plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a		15. Elevation (Show whether	DF, RT, GR, etc.)	12. County	
PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE ORILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CHANGE PLANS CHANGE PLANS CHANGE PLANS COMMENCE ORILLING OPNS. PLUG AND ABANDONMENT COMMENCE ORILLING OPNS. CASING TEST AND CEMENT JGB OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sack plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a		4074' DF	4057' GL	Lea	
OTHER OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sack plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	NOTICE O	F INTENTION TO:	SUBSEQU	JENT REPORT OF:	57
Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sack plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	<u> </u>			PLUG AND	ABANDONMENT
Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sack plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	PULL OR ALTER CASING	CHANGE PLANS		1	
Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sack plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a			OTHER	· · · · · · · · · · · · · · · · · · ·	
Drilled to TD of 15,038', set 13-3/8" csg. at 384' with 400 sacks cement and 9-5/8" csg. at 4530' with 1100 sacks cement. Spotted 35 sack cement plugs in 8-3/4" hole from 14,787' to 14,872', 10,419' to 10,504', 9605' to 9690'. 25 sack cement plugs from 8070' to 8130', 5860' to 5950', in 9-5/8" csg. and 8-3/4" hole from 4502' to 4562'. Shot 9-5/8" csg. off at 1095'. Pulled and recovered 34 jts. 9-5/8" OD csg. Set 25 sack cement plug in 12-1/4" hole and 9-5/8" csg. from 1074 to 1116'. Spotted 25 sacks cement in 13-3/8" csg. and 12-1/4" hole from 369' to 411' and 10 sack plug from 0 to 10' in top of 13-3/8" csg. with 4" x 6' dry hole marker. Completed as a	OTHER				
	Drilled to TD of csg. at 4530' wi from 14,787' to from 8070' to 81 4562'. Shot 9-5 Set 25 sack cement from 0 to 10' in	E 15,038', set 13-3/8" csg. th 1100 sacks cement. Spot 14,872', 10,419' to 10,504' 30', 5860' to 5950', in 9-56/8" csg. off at 1095'. Pullent plug in 12-1/4" hole and in 13-3/8" csg. and 12-1/4' top of 13-3/8" csg. with 4	at 384' with 400 sack ted 35 sack cement p , 9605' to 9690'. 2: 5/8" csg. and 8-3/4" 1 1ed and recovered 34 1 9-5/8" csg. from 10' 1 hole from 369' to 4	ks cement and 9- lugs in 8-3/4" h 5 sack cement pl hole from 4502' jts. 9-5/8" OD 74 to 1116'. Sp 11' and 10 sack	5/8" ole ugs to csg. otted plug

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 11 12 13 14 15 DATE February 25, 1970

APPROVED BY JAM W. ALMYMAN TITLE 12 DATE

CONDITIONS OF APPROVAL, IF ANY: