

| | | |
|------------------------|--|--|
| NO. OF COPIES RECEIVED | | |
| DISTRIBUTION | | |
| SANTA FE | | |
| FILE | | |
| U.S.G.S. | | |
| LAND OFFICE | | |
| OPERATOR | | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|---|---|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Adobe Oil & Gas Corporation 3. Address of Operator 1100 Western United Life Bldg., Midland, TX 79701 4. Location of Well UNIT LETTER G 1980 FEET FROM THE N LINE AND 1980 FEET FROM THE E 20 LINE, SECTION 14-S RANGE 36-E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3954 GR | 7. Unit Agreement Name 8. Farm or Lease Name Head State 9. Well No. 1 10. Field and Pool, or Wildcat Austin, Mississippian 12. County Lea |
|---|---|

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17½" hole @ 12:15 p.m. 10/17/80. Drld to 383' KB & cemented 387.55' of 13-3/8" 61#/ft csg @ 383' w/450 sx Class "C" cement w/2% CaCl. Cement circulated. Plug down @ 9:30 p.m. 10/17/80. Tested csg to 600# for 30 min w/no loss.

Drld 11" hole to 4650' on 10/23/80. Ran 1306.22' 8-5/8" 32# K-55 csg 1165.91' of 28# 8-5/8" csg 2203.24' 8-5/8" 24# K-55 csg & set @ 4650'. Cemented w/2200 sx Howco Lite cement w/10# salt & 5# Gilsonite/sx + 300 sx Class "C" w/2% CaCl. POB 7:30 a.m. 10/24/80. Circ 350 sx cement. Cut off & NU. Tested csg to 1000# for 30 min w/no pressure loss.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bill Owens Bill Owens

TITLE Engineer

DATE 10/27/80

APPROVED BY Jerry Sexton
Disc 1-5-80

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

OCT 28 1980

OIL CONSERVATION DIV.