

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

NONE

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REELEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Hilliard Oil and Gas, Inc.

3. Address of Operator
3000 N. Garfield, Suite 120 Midland, Texas 79701

4. Location of Well
UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM
THE West LINE, SECTION 26 TOWNSHIP 12S RANGE 37E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3890.1 GR

7. Unit Agreement Name

NONE

8. Form of Lease Name

Moss FNB

9. Well No.

1

10. Field and Pool, or Wildcat

S.W. Gladiola, Dev.

12. County

Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPS. ☐

PLUG AND ABANDONMENT ☒

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On November 22nd Mr. Jerry Sexton was contacted--The following plugs were given in order to plug & abandon the well.

Plug #1 - 200' plug at 10,200' - 85 sx class "H" neat
Plug #2 - 100' plug at 9,230' - 50 sx class "H" neat
Plug #3 - 100' plug at 7,905' - 50 sx class "H" neat
Plug #4 - 100' plug at 5,918' - 50 sx class "H" neat
Plug #5 - 100' plug at 4,440' - 30 sx class "H" neat - 8-5/8" set at 4,440'
Plug #6 - 100' plug at 2,228' - 30 sx class "H" neat Plug 50' inside - 50' outside
Plug #7 - 10 sx at surface.

A balanced plug method was used in placing these plugs.
Halliburton-Hobbs was the cementing company.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

Robert E. Patterson
Robert E. Patterson

TITLE

Drilling Engr.

DATE

11-23-82

APPROVED BY

Ronald M. Coulter
RONALD M. COULTER
OIL & GAS INSPECTOR

DATE

FEB 22 1983

CONDITIONS OF APPROVAL, IF ANY: