

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Per <input type="checkbox"/>
5. State Oil & Gas Lease No.	
V-773	
7. Unit Agreement Name	
8. Farm or Lease Name	
State DZ	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Wildcat	
12. County	
Lea	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER: Dry Hole

2. Name of Operator  
Cities Service Oil & Gas Corp.

3. Address of Operator  
P.O. Box 50250 *Midland TX 79710*

4. Location of Well  
UNIT LETTER N 330 FEET FROM THE South LINE AND 1650 FEET FROM THE West LINE, SECTION 23 TOWNSHIP 12S RANGE 38E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
3792' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 12650' Dolomite, Lime & Shale. Plugged and Abandoned. Drilled a 7-7/8" hole from 4500' to a T.D. of 12650' in Dolomite, Lime and Shale and plugged and abandoned this well in the following manner:

1. Spotted a 50 sack Class H cement plug @ 12614 - 12514'.
2. Spotted a 50 sack Class H cement plug @ 12148 - 12048', across the top of the Devonian.
3. Spotted a 50 sack Class H cement plug @ 9721 - 9621', across the top of the Cisco.
4. Spotted a 50 sack Class H cement plug @ 7875 - 7775', across the top of the Abo.
5. Spotted a 50 sack Class H cement plug @ 5913 - 5813', across the top of the Glorieta.
6. Spotted a 50 sack Class H cement plug @ 4551 - 4451', 1/2 in and 1/2 out of the 9-5/8" casing shoe @ 4500'.
7. Spotted a 50 sack Class H cement plug @ 2007 - 1907', across the top of the salt.
8. Spotted a 50 sack Class H cement plug @ 462 - 362', 1/2 in and 1/2 out of the 13-3/8" casing shoe @ 400'.
9. ND BOP, ND WH, cut off WH and spotted a 10 sack Class H cement surface plug @ 30 - surface and installed a 4" dry hole marker 4' above the ground to designate a plugged and abandoned location.

This plugging procedure was verbally approved by Mr. Paul Couch w/NMOCD on 12-03-87.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>J.A. Vitans</u>	TITLE <u>Dist. Opr. Mgr. - Prod.</u>	DATE <u>12-11-87</u>
APPROVED BY <u>Jack Griffin</u>	TITLE <u>OIL &amp; GAS INSPECTOR</u>	DATE <u>JUL 28 1988</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

DEC 17 1987

OCD  
HOLLIS LANCE