

4 1/2" liners, 18" stroke. Compound driven
 Pump No. 2: Emsco DB500 500 H.P. powered by D379
 Caterpillar Diesel.

DRILL STRING

4,500' 4 1/2" Grade E, 20-lb.
 9,000' 4 1/2" Grade E, 16.60-lb.
 Tool Joints: 4 1/2" XH, 6 1/4" OD.
 Twenty-Seven drillcollars 8 1/4" OD, 2 1/4" ID.
 Twenty-One 8" OD x 2 1/2" ID Drill Collars
 Other sized drillpipe and drillcollars available.

BLOWOUT PREVENTERS

One Shaffer LWS hydraulic double 11" x 5,000 p.s.i. One
 Hydri 11" x 5,000 p.s.i. Choke manifold 4" x 5,000 p.s.i.
 flanged connections. Koomey Type 80, 7-station
 accumulator closing unit with remote control.

SWIVEL. Brewster No. 350 10h

ROTARY TABLE. Oilwell 20 1/2"

SHALE SHAKER. Totco double screw

ELECTRICAL POWER. Two 135-kw /
 powered by diesel engines. AC fluors
 mercury vapor lights. All vapor-proof.

FRESH WATER STORAGE. Two 500

HOUSING. One 10' x 44' refrigerated
 house with sleeping and cooking facil

