

PLUGS AND ADAPTERS

Heaving plug--Material Length Depth set

Adapters--Material Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
3 1/2"		Nitro	140 lbs	7-12-49	3614-3685	3960'

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 3960' feet, and from feet to feet

DATES

....., 19..... Put to producing 19.....

The production for the first 24 hours was barrels of fluid of which % was oil; %

emulsion, % water, and % sediment. Gravity, °Bé.....

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Its pressure, lbs. per sq. in.

EMPLOYEES

Charles Pyatt Driller
 C.W. Hammond Driller
 Red Walter Driller

FORMATION RECORD

FROM	TO	TOTAL FEET	FORMATION
0	610	610	Red Bed
610	765	155	Sandy shale
765	837	72	Red sand, shale
837	1800	963	Sand
1800	1865	65	Sand
1865	1890	25	Sand
1890	1990	100	Sandy shale
1990	2055	65	Sandy + Red shale
2055	2950	895	Sandy shale
2950	2985	35	Red sand
2985	3241	256	Sandy shale
3241	3288	47	Sandy shale + fine
3288	3577	289	Grey Limestone
3577	3613	36	Sandy Limestone
3613	3622	9	Sand
3622	3690	68	Sand

(OVER)