

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

WELL RECORD

AREA 640 ACRES
LOCATE WELL CORRECTLY

LEONARD NICHOLS

(Company or Operator)

W.B. TRIMBLE "O"

(Lease)

Well No. 5, in SW $\frac{1}{4}$ of SE $\frac{1}{4}$, of Sec 11, T. 17, R. 32, NMPM.

NAJAMAP

Pool, LEA

County.

Well is 1960 feet from EAST line and 330 feet from SOUTH lineof Section 11-17-32If State Land the Oil and Gas Lease No. is FEFDrilling Commenced 4.30.1963, 19..... Drilling was Completed 5.7.1963, 19.....Name of Drilling Contractor ROD RIC CORP.Address MIDLAND, TEXASElevation above sea level at Top of Tubing Head 4107 The information given is to be kept confidential until

....., 19.....

OIL SANDS OR ZONES

No. 1, from 3965 to 3974 No. 4, from 4104 to 4114No. 2, from 4086 to 4093 No. 5, from toNo. 3, from 4096 to 4100 No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24	NEW	332	REG.			
5 1/2	14	USED	4150	FLOAT		3965-74	
						4086-93	
						4096-4103	

4104-4114

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/4	8 5/8	332	225	HALLIBURTON		
7 7/8	5 1/2	4150	325	HALLIBURTON		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

20000 GAL. REFINED OIL 40000 LBS. SANDResult of Production Stimulation 68 BBL. OIL 24 HOURS

Depth Cleaned Out.....

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 4150 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing MAY 5.1963, 19
OIL WELL: The production during the first 24 hours was 68 barrels of liquid of which 98% was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.		T. Devonian	T. Ojo Alamo
T. Salt. 1195		T. Silurian	T. Kirtland-Fruitland
B. Salt. 2305		T. Montoya	T. Farmington
T. Yates		T. Simpson	T. Pictured Cliffs
T. 7 Rivers		T. McKee	T. Menefee
T. Queen. 3148		T. Ellenburger	T. Point Lookout
T. Grayburg. 3380		T. Gr. Wash	T. Mancos
T. San Andres. 4115		T. Granite	T. Dakota
T. Glorieta		T.	T. Morrison
T. Drinkard		T.	T. Penn.
T. Tubbs		T.	T.
T. Abo		T.	T.
T. Penn.		T.	T.
T. Miss.		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1195	1195	GYP & RED BED				
1195	2305	1110	SALT				
2305	3348	1043	ANHYDRITE				
3348	3388	40	RED SAND				
3388	3680	292	ANHYDRITE				
3680	3965	277	LIME				
3965	3974	9	SANDY LIME OIL PAY				
3974	4088	112	LIME				
4088	4114	26	SANDY LIME OIL PAY				
4114	4150	36	LIME				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator. LEONARD NICHOLS
Name. O.L. McCUTCHEN
Address. WALJAMAR, NEW MEXICO
Position or Title. Supt.
MAY 20. 1963 (Date)