

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 059 001

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

7. UNIT AGREEMENT NAME

MCA Unit Repr.

8. FARM OR LEASE NAME

MCA Unit

9. WELL NO.

275

10. FIELD AND POOL, OR WILDCAT

MAIT. G-SA Repress.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 33, T17S, R32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3961' DF

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

"See Attached Sheet"

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Burt

TITLE

Admin. Supv.

DATE

5-18-77

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

USGS(5) MCA(4) File

ACCEPTED FOR RECORD

MAY 20 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

RECEIVED

APR 2 1971

U.S. DEPARTMENT OF AGRICULTURE
WASHINGTON, D.C. 20250

MCA Unit 275
1345' FNL & 660' FEL of Sec 33

10 BWP

DAILY ALLOW: UNIT ALLOW
WORK STARTED: 8-26-76

DAILY ALLOW: UNIT ALLOW
WORK COMPLETED: 9-18-76

WORK DONE: PULLED PRODUCING EGPT. RAN CBL-VOL BOND LOG, 3843-1000'. PERF 2450-51 W/2 JS SQUEEZED W/125 SX CLASS "C" CMT, 2% CACL AND 3#/SX SALT. AIR 2 BPM AT 1400#. DISPLACED W/16-1/2 BW AT 1100#. HELD 1300# ON CMT. LOGGED FROM 2400-1500'. TOC AT 2220'. D.O. CMT 2379-2451'. TSTD SQUEEZE, SLIGHT BACKFLOW. BROKE DOWN FORMATION AT 2150#. SQUEEZED W/150 SX CMT, 2% CACL, 3#/SX SALT. DISPLACED W/15.5 BW. PERF 1124-25' W/2 JET SHOTS. TSTD CSG TO 1000#. PMPD DOWN TBG AT 6-1/2 BPM W/1700#. SQUEEZED W/150 SX HOWCO THIK-SET, 2#/SX FLOCLE, FOLLOWED W/150 SX CLASS "C" CMT, 2% CACL AND 3#/SX SALT. AIR 3 BPM AT 1100#. DISPLACED W/7.5 BW. D.O. CMT. 1047-1155'. TSTD CMT TO 300#. O.K. TSTD FOR BACKFLOW. F.L. RAISED 100' IN 30 MIN. LOADED HOLE W/FW AT 1 BPM W/1500# SQUEEZED W/150 SX CLASS "C" CMT, 2% CACL AND 3#/SX SALT. AIR 1.25 BPM AT 1400#. FLUSHED W.7 BW. D.O. CMT 1015-1145'. TSTD TO 500#. O.K. SWBD DRY TO 1100'. F.L. RAISED 300'. PMPD 9 BEL BRINE DOWN TBG. AIR 1 BPM AT 2500#. FLUSHED W/6 BFW. PMPD 12 BELS HOWCO SPECIAL GELLING AGENT. AIR 1-1/2 BPM AT 2300#. BROKE TO 2000# AT 1 BPM. PMPD 2 BELS FORM STOPPED TAKING FLUID. PRESSURED TO 3000#. REVERSE CIRC GEL. TSTD TO 3000#. O.K. SWBD DRY. F.L. RAISED 200' OVERNIGHT. SQUEEZED W/4.7 BELS CLASS "C" CMT, 2% CACL AND 3#/SX SALT. DISPLACED W/5-1/4 BFW. TSTD CMT TO 2500#. PRESS BLEED OFF TO 100# IN 30 MIN. D.O. CMT 1030-1134'. PMPD 250 GAL 15% HCL ACID. AIR 4.8 BPM AT 1600#. SQUEEZED W/130 SX CMT, 2% CACL, 3#/SX SALT. AIR 2.4 BPM AT 1400#. FLUSHED W/7.75 BW. TSTD TO 2000#. O.K. D.O. CMT 953-1036'. SWBD DRY. NO BACKFLOW ON TBG. BACKFLOW ON CSG AT 500#. PERF 949-950 W/2 JET SHOTS. PMPD 100 SX THIK-SET AND 25 SX CLASS "C" CMT, 2% CACL. AIR 2 BPM AT 2000#. DISPLACED W/7 BFW. SHUT-IN W/1000# ON TBG. SLIGHT BACKFLOW ON CSG. ANNULUS. D.O. CMT 830-953' AND 2275-2734'. LAID DN WORKSTRING, PKR AND RBP. RAN PRODUCING EGPT. P.O.P.

LOCATION: 1345' FNL & 660' FEL OF SEC. 33, T-17S, R-32E.

USGS(5). MCA (4). File

RECEIVED

172.97

10/12/2001