

COPIES RECEIVED		
TRIBUTION		
FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Hondo Drilling Company	8. Farm or Lease Name Hondo Fee
3. Address of Operator P.O. Drawer 2516 Midland, Texas 79702	9. Well No. #1
4. Location of Well UNIT LETTER <u>L</u> <u>1980'</u> FEET FROM THE <u>South</u> LINE AND <u>660'</u> FEET FROM THE <u>West</u> LINE, SECTION <u>19</u> TOWNSHIP <u>16-S</u> RANGE <u>36-E</u> N.M.P.M.	10. Field and Pool, or Wildcat <u>undesignated</u> <u>North Shoe Bar</u>
15. Elevation (Show whether DF, RT, GR, etc.) 3963' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

June 29 to July 2, 1979 Drilling 11" surface hole from 366' to 4250' total depth 11" surface hole at 1:30 PM. Ran 47 jts 8 5/8" csg 2015' 24# K-55 ST &C; and 54 jts 32# K-55 ST &C 2245'; total of 101 joints and 4260' of 8 5/8" pipe. Set at 4250' cemented with 1700 sks of HowCo light cmt and 200 sks of Class "C" neat. Plug down at 9:55 PM.

July 3, 1979 Ran Temperature Survey top of cement at 500'. Cemented outside 8 5/8" casing thru 1" pipe with 150 sks of regular cement. Cement circulated at 12:15 PM. Set slips on 8 5/8" casing. W.O.C. total of 24 hours. Pressure tested blowout preventers and 8 5/8" casing 3000# pressure and drilling cement plug.

July 4, 1979 Drilling 7 7/8" hole at 4327'.

I, hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: Jerry Sexton TITLE: Landman DATE: July 9, 1979

APPROVED BY: Jerry Sexton TITLE: Dist. 1, Supv. DATE: JUL 11 1979

RECEIVED  
JUL 10 1970  
O.C.D. HOBBS, OFFICE