

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 3D-025-31242
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V2454
7. Lease Name or Unit Agreement Name West Kennitz
8. Well No. 1
9. Pool name or Wildcat West Kennitz Wolfcamp
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4242.6 GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER P & A
2. Name of Operator Read & Stevens, Inc.
3. Address of Operator P.O. Box 1518, Roswell, NM 88202
4. Well Location Unit Letter <u>A</u> : <u>860</u> Feet From The <u>N</u> Line and <u>660</u> Feet From The <u>E</u> Line Section <u>36</u> Township <u>16S</u> Range <u>32E</u> NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 7 7/8" hole @ 10,974'. Notify the State and receive plugging instructions. Set cmt plugs as follows:

- 1) Kennitz Reef 10,780-10,680
- 2) Abo 7,830-7,730
- 3) Glorietta 5,800-5,700
- 4) 8 5/8" shoe 4,555-4,455
- 5) Salt 1,294'-1,194'
- 6) 10' surface plug.

Good circ on all plugs using 9.2 ppg mud laden fluid. Install DH marker, RDMORT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John C. Maxey, Jr. TITLE Petroleum Engineer DATE 8-19-91
 TYPE OR PRINT NAME John C. Maxey, Jr. TELEPHONE NO. 505/622-3770

(This space for State Use)

APPROVED BY Cary W. Hill TITLE OIL & GAS INSPECTOR DATE JUL 09 '92
 CONDITIONS OF APPROVAL, IF ANY:

87-21-98
 PG dated 7-9-92 E