

DISTRICT I P. O. Box 1980, Hobbs, NM 88240

DISTRICT II P. O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION P. O. Box 2088 Santa Fe, NM 87504-2088

WELL API NO. 30-025-34064

5. Indicate Type of Lease STATE [] FEE [x]

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name Maljamar Grayburg Unit

1 Type of Well: OIL WELL [x] GAS WELL [] OTHER []

8. Well No. 128

2. Name of Operator The Wiser Oil Company

9. Pool name or Wildcat Maljamar Grayburg San Andres

3. Address of Operator P.O. Box 2568 Hobbs, New Mexico 88241

4. Well Location Unit Letter C : 660 Feet From The North Line and 1830 Feet From The West Line Section 4 Township 17S Range 32E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4186' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data. NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK [], PLUG AND ABANDON [], TEMPORARILY ABANDON [], PULL OR ALTER CASING [], OTHER: []. SUBSEQUENT REPORT OF: REMEDIAL WORK [], ALTERING CASING [], COMMENCE DRILLING OPNS. [], PLUG AND ABANDONMENT [], CASING TEST AND CEMENT JOB [], OTHER: Perforate, Acidize & Frac [x]

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 10/30/97 HES perforated Vacuum f/4116', 17', 18', 19', 20', 21', & 22' w/2 SPF (14 holes). HES acidized San Andres Vacuum perms. f/4116'-4122' w/2400 gals. 15% NE-FE acid & 28 ball sealers. Formation broke @ 2951#. ATP 2450# @ 4.5 bpm. MTP 2724# @ 5.8 bpm. Balled out w/4493#. ISIP 2236#. 5 min. 2149#. 10 min. 2114#. 15 min. 2088#. HES ran WLSRBP & set @ 4080'. Perforated Grayburg f/3895', 97', 3908', 29', 40', 41', 51', 52', 59', 60', 66', 78', 86', 88', 89', 90', 4024', 25', 26', 32', 33', 41', 48', 49', 51', 54', 55', 58' & 59' w/1 SPF (29 holes). HES acidized Grayburg perms. 3895'-4059' w/3000 gals. 15% NE-FE acid & 58 ball sealers. Formation broke @ 1381#. ATP 2320# @ 5.2 bpm. MTP 2555# @ 7.1 bpm. Balled out w/4227#. 11/05/97 HES frac'd Grayburg perms. 3895'-4059' w/12,000 gals. gelled water, 40,000 gals. 20# Delta Frac & 100,000# 16/30 Brady sand. ATP 3598# @ 56 bpm. MTP 3713# @ 60 bpm. ISIP 3240#. 5 min. 2840#. 10 min. 2684#. 15 min. 2540#. 11/07/97 MIRU unit. Installed WH & BOP. RIH w/127 jts. 2-7/8" tbg. Tagged sand @ 3977'. Cleaned out sand f/3977'-4071'. Pulled above perms. w/tbg. to 3854'. 11/10/97 RIH w/tbg. Tagged @ 4017'. Cleaned out sand f/4017'-4077'. RIH w/tbg. & retrieved RBP @ 4080'. POH w/RBP. 11/11/97 RIH w/124 jts. 2-7/8" tbg. Tbg. @ 3888'. SN @ 3889'. TAC @ 3793'. RIH w/rods & 2-1/2" x 1-1/2" x 16' RHTC pump. Left well pumping to Battery.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mary Jo Turner TITLE Completion Department DATE Decemberr 20,1998

TYPE OR PRINT NAME: Mary Jo Turner TELEPHONE NO. (505) 392-9797 (This space for State Use)

APPROVED BY ORIGINAL SIGNED BY CHRIS WILLIAMS DISTRICT I SUPERVISOR TITLE DATE

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____ 3320'	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____ 3730'	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 4064'	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs _____	T. Entrada _____	T. _____
T. Abo _____	T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from to No. 3, from to
 No. 2, from to No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.....
 No. 2, from to feet.....
 No. 3, from to feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	450'	450'	Caliche & sand				
450'	1050'	600'	Redbed				
1050'	1200'	150'	Anhydrite				
1200'	2200'	1000'	Salt				
2200'	4500'	2300'	Dolomite, sand & anhydrite				

4
MAR 1958
Received
Hobbs
OCD