

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-34683
1 Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5 Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2 Name of Operator Charles B. Gillespie, Jr.		6 State Oil & Gas Lease No. 04688
3 Address of Operator P.O. Box 8, Midland, Texas 79702		7 Lease Name or Unit Agreement Name State "D"
4 Well Location Unit Letter <u>U</u> : 330 Feet From The <u>South</u> Line and 330 Feet From The <u>West</u> Line 1 Section 16S Township 35E Range NMPM Lea County		8 Well No. 9 9 Pool name or Wildcat Big Dog Strawn, South
10 Elevation (Show whether DF, RKB, RT, GR, etc.) GR - 3977'		

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ANBANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER: _____ <input type="checkbox"/>		OTHER: _____ <input type="checkbox"/>	

12 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10/03/99 Finished drilling 11" hole to 4757'. Run 118 jts 8-5/8" 32#, J-55 & M-80 csg to 4757'.

10/04/99 Cement 8-5/8" csg w/1250 sxs class "C" 50/50 poz w/10% bentonite followed by 200 sxs class "C" w/1% CaCl2. Plug down @ 8:24 AM 10/03/99. Circ 240 sxs to pits. ND BOPs. Set slips. Cut off csg. Weld on head. NU BOPs. PU & RIH w/7-7/8" bit. Test BOPs & csg to 1500 psi. DO cmt and formation 15 hrs after plug down.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mark Mladenka TITLE Production Manager DATE 10-05-99
 TYPE OR PRINT NAME Mark Mladenka TELEPHONE NO. (915)683-1765

(This space for State Use)

ORIGINAL SIGNED BY
GARY WINK
FIELD REP II

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

5

✓