(SUBMIT IN TRIPLICATE)

U. S. Land Office LAR OFFICES
Lease or permit No. OGO488
S. A. BOURSE

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DOUL	l l	1			1 -
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF			
NOTICE OF INTENTION TO CHANGE PLA	ANS	SUBSEQUENT	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING		
OTICE OF INTENTION TO TEST WATER	R SHUT-OFF	SUBSEQUENT	REPORT OF ALTERING	CASING	
IOTICE OF INTENTION TO RE-DRILL OF	R REPAIR WELL	SUBSEQUENT	REPORT OF REDRILLING	G OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR A	ACIDIZE	SUBSEQUENT	REPORT OF ABANDONM	ENT	
NOTICE OF INTENTION TO PULL OR AL	TER CASING	SUPPLEMENT	ARY WELL HISTORY		
NOTICE OF INTENTION TO ABANDON W	YELL				
(INDICATE	ABOVE BY CHECK MARK	NATURE OF REPORT	r, notice, or other da	ra)	(,
			Cotobez	14,	, 19.4
ell No is loca	ated 669 ft. fro	om N line an	d 1980 _ft. from	line of se	c. 28
W/4 of 300, 28 (4 Sec, and Sec, No.)	19-3 (Twp.)	(Range)	(Meridian)	•••	
Fost Insk	T.A.			. Marri aa	
(Field)	(County	or Subdivision)	(5	State or Territory)	••
	objective sands; show siz ing points, and all c		gths of proposed casings posed work)		
Han 8 5/6 ith 50 ex. of come surface. Let se rilling plug. Dri ale tested dry se	bijective sands; show size ing points, and all common procedures to procedure to pr	to 928 to	and camente and camente and heavy illed hole d water shut	d by Hall mud sireu ry before -off belovemented 1	iburt ikted w sho
Ren 8 5/6 ith 50 ex. of come surface. Let se rilling plug. Dri ale tested dry se	bijective sands; show size ing points, and all of the sand all	to 928 to	and camente and camente and heavy illed hole d water shut	d by Hall mud sireu ry before -off belovemented 1	iburt ikted w sho
Ren 8 5/6 ith 50 ex. of come surface. Let se rilling plug. Dri ale tested dry se	bijective sands; show size ing points, and all common procedures to procedure to pr	to 928 to	and camente and camente and heavy illed hole d water shut	d by Hall mud sireu ry before -off belovemented 10	iburt ikted w sho
Ren 8 5/6 ith 50 ex. of come surface. Let se rilling plug. Dri ale tested dry se	bijective sands; show size ing points, and all common procedures to procedure to pr	to 928 to	and camente and camente and heavy illed hole d water shut	d by Hall mud sireu ry before -off belovemented 10	lburt inted
Ren 8 5/6 th 50 ex. of cene c surface. Let se rilling plug. Dri ale tested dry se lug drilled out 10	bijective sands; show size ing points, and all conting points, and all conting ent preceded at for 72 hilled plug at started ario (10/42. No.	to 988 to 988 to 988 and to 988 to 98	and camente and camente and camente and camente and camente alled hole d water shut ad. Well o	d by Hall: mud circul ry before -off below emented 10 ow pipe.	iburt inted w sho
Hen 8 5/6 ith 50 fx. of ceme o surface. Let so rilling plug. Dri ale tested dry so lug drilled out 10	bijective sands; show size ing points, and all conting points, and all conting ent preceded at for 72 hilled plug at started arisolate. No	to 928 to	and camente and camente and camente and camente and camente alled hole d water shut ad. Well c a shead bel	d by Hall: mud circul ry before -off below emented 10 ow pipe.	iburt inted w sho
Ran 8 5/6 ith 50 ex. of come o surface. Let so rilling plug. Dri ale tested dry so lug drilled out 10 understand that this plan of work m	bijective sands; show size ing points, and all control of the process of the proc	to 928 to	and camente and camente and camente and camente and camente alled hole d water shut ad. Well c a shead bel	d by Hall: mud circul ry before -off below emented 10 ow pipe.	iburt inted w sho
ith 50 ex. of come o surface. Let so rilling plug. Dri sic tested dry so	bijective sands; show sisting points, and all conting points, and all conting entire proceedings of for 72 hilled plug a started drift of 10/42. Note that the started drift of 10/42.	to 928 to	and camente and camente and camente and camente and camente alled hole d water shut ad. Well c a shead bel	d by Hall: mud circul ry before -off below emented 10 ow pipe.	iburt inted w sho

The setting of the set

- SETATT GROUP.

1.另一個問題的人名印度特別發展的過程的

PRIVACE CACCELERATE

LER BURGATE OF BURK BURGES TO COLUMN

to the Maria of the solid probability of the s

Model Control of the Co

en de la Santana de Caractería de la Car

開発しる 当時 引き与るにはなっ

in the control of the

المراجعة ال المراجعة ال

கார் நடித்திருள்ள குறிய இருந்திருள்ள முறிய நடித்திருள்ள இருந்திருள்ள குறிய முறிய குறிய கு

(SUBMIT IN TRIPLICATE)

U. S. Land Office OSO488

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

Well No. 2 is located 660 ft. from N line and 1980 ft. from W line of sec. 28 14 of MW/4 of Sec. 28 19-3 82-E MMPM (4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Rest Lank Lon Hew Mexico . (Field) (County or Subdivision) (State or Territory)	NOTICE OF INTENTION TO CHANGE PLANS. NOTICE OF INTENTION TO TEST WATER SHUT-OFF. NOTICE OF INTENTION TO RE-ORILL OR REPAIR WELL. NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO ABANDON WELL. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) October 8, Well No. is located 660 ft. from Notice of Intention of Abandon Mell. (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) October 8, Well No. (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) October 8, Well No. (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) October 8, Well No. (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) October 8, Well No. (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA) (Indicate Above By Check Mark Nature of Report, Notice, OR OTHER DATA)		
NOTICE OF INTENTION TO TEST WATER SHUT-OFF. NOTICE OF INTENTION TO REDRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) October 8, 19.4 Well No. is located 660 ft. from Notice of the data is located 660. (It see, and see, No.)	NOTICE OF INTENTION TO TEST WATER SHUT-OFF	ION TO DRILL SUBS	QUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) October 8, 19.4 Well No. is located 660 ft. from N line and 1960 ft. from W line of sec. 26 (A OC MW/A OC Sec. 28 19-3 32-E MAPM (A Sec. 28 19-3	NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO DEANDON WELL. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) October 8, Well No. 2 is located 60 ft. from 8 line and 1980 ft. from W line of sec. 14 of 84/4 of 3ec. 28 19-3 32-E REPM (It Sec. and Sec. No.) (Twp.) (Range) (Meridian) Fast Lines (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 3875 ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and length of proposed casings; indicate mudding job ing points, and all other important proposed work.) Top of Anhydrite 800°. Ran 8 5/8° Op casing to 928° and cases the 50 Sx. of cases by Balliburton proceeded by heavy mud of the surface. Will let stand 72 hrs. before testing where short and arilling plug. Work done 10/7/42.		QUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	Well No. 2 is located 600 ft. from Siline and 1960 ft. from Willing of sec. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) October 8, Well No. 2 is located 600 ft. from Siline and 1960 ft. from Willine of sec. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) October 8, Well No. 2 is located 600 ft. from Siline and 1960 ft. from Willine of sec. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) October 8, Well No. 2 is located 600 ft. from Siline and 1960 ft. from Willine of sec. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) October 8, Well No. 2 is located 600 ft. from Siline and 1960 ft. from Willing Siline and 1960 ft. from Williams (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) October 8, Well No. 2 is located 660 ft. from Siline and 1960 ft. from Williams (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) (INDICATE ABOV	ION TO TEST WATER SHUT-OFF	QUENT REPORT OF ALTERING CASING.
Well No	Well No. 2 is located 650 ft. from line and 1930 ft. from line of sec.	ION TO RE-DRILL OR REPAIR WELL SUBS	QUENT REPORT OF REDRILLING OR REPAIR
Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data) Well No. is located 660 ft. from Notice, or other data is located for median in located 660 ft. from Notice, or other data is located ft. from Notice, or other data is loc	Well No is located 660ft. from line and 1980ft. from line of sec. LA of MW/A of Sec. 38 19-3	ION TO SHOOT OR ACIDIZE	QUENT REPORT OF ABANDONMENT
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Cotober 6, 19.4 Well No. is located 660 ft. from N line and 1800 ft. from W line of sec. 28 LA OF W/4 of Sec. 28 19-3 82-E RAPM (A Sec. and Sec. No.) (Twp.) (Range) (Meridian) Rest Insk Hew Mexico. (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 38.75 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and all other important proposed work) Rop of Anhydrite 800 Ran 8 5/8 OD cessing to 928 and cements of the Surface Will let stand 78 hrs. before testing	(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) October 8, Well No. 8 is located 660 ft. from Notice of the form Notice of the form of the derick floor above sea level is 38-75 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding job ing points, and all other important proposed work) Top of Ambydrite 800°. Ran 8 5/8° OD casing to 928° and cancer the 50 Sz. of casent by Helliburton proceeded by heavy mud circulated to the surface. Will let stand 72 hrs. before testing mater shut off and crilling plus. Work done 10/7/42.	ION TO PULL OR ALTER CASING SUPP	EMENTARY WELL HISTORY
Well No is located 660 ft. from No line and 1860 ft. from No line of sec. 28 LA OF HW/4 of Sec. 28 19-3	Well No. is located 660 ft. from N line and 1980 ft. from W line of sec. 1/4 of HW/4 of Sec. 28 19-3 82-2 HBPM (1/4 Sec. and Sec. No.) (Twp.) (Rango) (Meridian) Rest Linek (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 3875 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and longths of proposed casings; indicate mudding job ing points, and all other important proposed work) Rept of Anhydrite 800°. Ran 6 5/8° OD casing to 928° and cannot the 50 Sx. of coment by Halliburton preceded by heavy mud oil related to the surface. Will let stand 72 hrs. before testing water shut off and drilling plus. Work done 10/7/42. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be come Company. Calbertson & Irwin, Inc.	ION TO ABANDON WELL	
Well No is located 660 ft. from No line and 1860 ft. from No line of sec. 28 LA OF HW/4 of Sec. 28 19-3	Well No. is located 660 ft. from N line and 1980 ft. from W line of sec. 1/4 of HW/4 of Sec. 28 19-3 82-2 HBPM (1/4 Sec. and Sec. No.) (Twp.) (Rango) (Meridian) Rest Linek (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 3875 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and longths of proposed casings; indicate mudding job ing points, and all other important proposed work) Rept of Anhydrite 800°. Ran 6 5/8° OD casing to 928° and cannot the 50 Sx. of coment by Halliburton preceded by heavy mud oil related to the surface. Will let stand 72 hrs. before testing water shut off and drilling plus. Work done 10/7/42. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be come Company. Calbertson & Irwin, Inc.		
Well No is located 660ft. from No line and 1860ft. from No line of sec. 28 1/4 of MW/4 of Sec. 28 19-5	Well No. 2 is located 660 ft. from N line and 1980 ft. from W line of sec. (A of NW/4 of Sec. 28 19-3 82-E NMPM (34 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Rast Link Lea Hew Mexico. (Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 38-75 ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobing points, and all other important proposed work) Top of Anhydrite 800°. Han 5 5/8° OD easing to 928° and emast ith 50 Sx. of occupit by Halliburton preceded by heavy mud oil mulated to the surface. Will let stand 72 hrs. before testing where shout off and crilling plug. Work done 10/7/42. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be come Company. Culbertson a Trwin, Inc.	(Indicate above by Check Mark Nature of	REPORT, NOTICE, OR OTHER DATA)
(4 Sec, and Sec. No.) (4 Sec, and Sec. No.) (5 Sec. and Sec. No.) (6 Sec. and Sec. No.) (7 Sec. and Sec. No.) (8 Sec. and Sec. No.) (9 Sec. and Sec. No.) (10 Sec. and Sec. No.) (11 Sec. and Sec. No.) (12 Sec. and Sec. No.) (13 Sec. and Sec. No.) (14 Sec. and Sec. No.) (15 Sec. and Sec. No.) (16 Sec. and Sec. No.) (17 Sec. and Sec. No.) (18 Sec. and Sec. No.) (19 Sec. and Sec. No.) (10 Sec. and Sec. No.) (10 Sec. and Sec. No.) (10 Sec. and Sec. No.) (11 Sec. and Sec. No.) (11 Sec. and Sec. No.) (12 Sec. and Sec. No.) (14 Sec. and Sec. No.) (15 Sec. and Sec. No.) (16 Sec. and Sec. No.) (17 Sec. and Sec. No.) (17 Sec. and Sec. No.) (18 Sec. and Sec. No.) (18 Sec. and Sec. No.) (19 Sec. and Sec. No.) (20 Sec. and Sec. No.) (21 Sec. and Sec. No.) (22 Sec. and Sec. No.) (23 Sec. and Sec. No.) (24 Sec. and Sec. No.) (25 Sec. and Sec. No.) (26 Sec. and Sec. No.) (26 Sec. and Sec. No.) (27 Sec. and Sec. No.) (27 Sec. and Sec. No.) (28 Sec. and Sec. No.) (28 Sec. and Sec. No.) (29 Sec. and Sec. No.) (29 Sec. and Sec. No.) (20 Sec. and Sec. No.) (21 Sec. and Sec. No.) (22 Sec. and Sec. No.) (22 Sec. and Sec. No.) (23 Sec. and Sec. a	(% Sec. and Sec. No.) (* Mange) (* Meridian)		October 8, 194
(Field) (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is 5875. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and all other important proposed work) Rop of Anhydrite 800. Ran 8 5/8. OD casing to 988 and canenter with 50 Sx. of cament by Halliburton preceded by heavy mud circulated to the surface. Will let stand 78 hrs. before testing	The elevation of the derrick floor above sea level is 3875. The elevation of the derrick floor above sea level is 3875. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding job ing points, and all other important proposed work) Rop of Anhydrite 800°. Ran 8 5/8° OD casing to 928° and cement with 50 Sx. of cement by Halliburton preceded by heavy mud oil walated to the surface. Will let stand 72 hrs. before testing mater shut off and trilling plug. Work done 10/7/42. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be company. Gulbertson & Irwin. Inc.	4 of Sec. 28 19-3 52-1	MPM
The elevation of the derrick floor above sea level is 3875. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and all other important proposed work) Top of Anhydrite 800. Ran 8 5/8. OD casing to 928 and comented it is 50 Sx. of coment by Halliburton preceded by heavy mud circulated to the surface. Will let stand 78 hrs. before testing	The elevation of the derrick floor above sea level is 5875 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding job ing points, and all other important proposed work) Rop of Anhydrite 800°. Ran 8 5/8° OD casing to 928° and cannot sith 50 Sx. of cament by Halliburton proceeded by heavy mud cit rulated to the surface. Will let stand 78 hrs. before testing where short off and drilling plug. Work done 10/7/42. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be come. Company Quibertson & Irvin. Inc.	Sec. No.) (Twp.) (Range)	, and an a
The elevation of the derrick floor above sea level is 3875 DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and all other important proposed work) Top of Anhydrite 800. Ran 8 5/8. OD casing to 928 and comented it is 50 Sx. of coment by Halliburton preceded by heavy mud circulated to the surface. Will let stand 78 hrs. before testing	The elevation of the derrick floor above sea level is 3675 DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding job ing points, and all other important proposed work) Rop of Anhydrite 800°. Ran 6 5/8° OD casing to 928° and cannot sith 50 Sx. of cament by Halliburton proceeded by heavy mud circulated to the surface. Will let stand 78 hrs. before testing where shut off and drilling plug. Work done 10/7/42. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be company. Outbertson & Irvin, Inc.	i) (County or Subdivis	on) (State or Territory)
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, centing points, and all other important proposed work) Top of Anhydrite 800'. Ran 6 5/8" OD casing to 928' and camented the 50 Sx. of cement by Halliburton preceded by heavy mud circulated to the surface. Will let stand 78 hrs. before testing	DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding job ing points, and all other important proposed work) Rop of Anhydrite 800°. Ran 8 5/8° OD casing to 928° and cameral to 50 Sx. of cament by Halliburton preceded by heavy mud circulated to the surface. Will let stand 72 hrs. before testing mater shut off and drilling plug. Work done 10/7/42. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commonly Culbertson & Irwin, Inc.		ilias
ater shut our and ariting play. Hork down 10/4/42.	I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be common to the common of	the surface. Will let st	preceded by heavy mud cir- and 78 hrs. before testing
	Company Culbertson & Irvin, Inc.	off and drilling plug.	ork done 10/7/42.
	Company Gulbertson & Irwin, Inc.		
	Company Gulbertson & Irwin, Inc.	t this plan of work must receive approval in writing by	
Lunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	• •		the Geological Survey before onevations may be commanded
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commence Company Company			the Geological Survey before operations may be commenced
Company Culbertson & Irwin, Inc.	Midland, Texas. By Cotting	. 0. Box 1071	the Geological Survey before operations may be commenced
Company Gulbertson & Irwin, Inc. Address P. O. Box 1071	Title Prod. Supt.		2. 8.21.)

大大王等,如《中国》为《北京·新兴园》《野山麓、观泉、诗草》。[1] [1] [1] [1] [2]

en de la Carlo En la Carlo de la Carlo de

The state of the s

医韧带 医二氏病节组

A second of the control of the control

and the second s

ŝ