

APPROVED
MAR 13 1962
A. R. BRUNN
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
HUBBS OFFICE OCC
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
1962 APR 9 AM 7:28

Land Office _____
Lease No. 3-41 0-0
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

| | |
|--|--|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY |
| NOTICE OF INTENTION TO ABANDON WELL | Report of setting 8-3/4" 2 11-3/4" Csg. |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. _____ is located _____ ft. from [N] line and _____ ft. from [E] line of sec. _____
NE 1/4, Sec. 30
(1/4 Sec. and Sec. No.) 105 32.5 32.5
(Twp.) (Range) (Meridian)
_____ New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3541 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Run 320' 10-3/4" Csg. Cemented w/50 sacks cement

Run 350' 8-3/8" C. J. No cement

Set 350' 8-3/8" csg. Left 320' 10-3/4" Csg. in hole

Set plugs as follows: 2702' to 2800'

2800' to 2850'

2850' to 2950'

2950' to 3400'

and casing at surface & dry hole anchor set

Circulated hole w/75 oz mud before commencing cementing operation.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company A. R. BRUNN

Address 2107 Wilco Bldg.

Abilene, Texas

By

Title Owner