

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPI
(Other instructions
verse side)

FE*
re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 030437(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal MA "D"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Corbin-Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31, T-17S, R-33E

12. COUNTY OR PARISH 13. STATE

Lea New Mexico

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒

Dry Hole

2. NAME OF OPERATOR

Carper Drilling Company, Inc.

3. ADDRESS OF OPERATOR

Artesia, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

860' from North line and 810' from West line

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4004' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Total Depth 8904'

Plug back total depth 4400'.

This well was plugged and abandoned as follows:

10 sack cement plug from 4400'-4305' across perforations 4310'-4320'

10 Sack cement plug from 3695'-3600' across perforations 3670'-3680'.

10 sack cement plug at surface with marker.

Heavy mud was used between plugs.

The following casing was left in the hole.

13 3/8" set at 225'.

8 5/8" set at 2779'.

5 1/2" from 2183' to 8898'.

65 joints (2170') 5 1/2" casing was recovered.

When location is ready for inspection the Hobbs U.S.G.S. will be notified.

18. I hereby certify that the foregoing is true and correct

SIGNED

William J. Foster

TITLE

Petroleum Engineer

DATE

12-12-64

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

APR 27 1965

*See Instructions on Reverse Side

**J. L. GORDON
ACTING DISTRICT ENGINEER**

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.