ATTACHMENT for COCKBURN STATE #1, form C-103, dated 3/18/80.

The Cockburn State A #1 wad drld in 1945, & operated by Barney Cockburn. We have no plugging information on this well. The NMOCD has recently ruled that several wells in this vicinity, including this well, are not properly plugged for the purpose of water injection. Since the NMOCD is now requiring anyone who is injecting water within ½ mile of these wells to replug the well bore, the responsibility rests with the Southeast Maljamar Grayburg-San Andres Unit.

RIH w/4 -3/4" RB. Tagged metal @ 1566'. Circ. & drld 9' to 1575'. Could get no deeper. RIH w/7-1/8" lead impression block on 2-7/8" EUE tbg. Tagged @ 1566'. Got good impression of 2-3/8" EUE tbg. body looking up. RIH w/5-3/4" O.S. w/oversize quide, 3-3/4" jars, 4 3½" DC's on 2-7/8" EUE tbg. POOH w/overshot.

Milled 15' to 1581'. RIH w/mule shoe tbg sub on 2-7/8" EUE tbg to 1650' without touching anything. Ran GR-CCL from 1662' to surface. Shows 7" csg stub at 1622' & 8-5/8" csg shoe at 1262'. Mixed & pmpd 200 sx Class C & displaced 1675 - 1284'.

Tagged cmt plug at 1313'. Mixed & pmpd 200 sx Class C & displaced 1313 - 956'. Tagged cmt plug at 1020'. Circ hole w/mud laden fluid. Displaced 10 sx cmt plug 30' to surface. Installed 4" dry hole marker. Mason Clegg w/NMOCD witnessed job.