

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

CITIES SERVICE OIL & GAS CORPORATION

3. ADDRESS OF OPERATOR

P. O. BOX 1919 - Midland, Tx. 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2310' FNL & 1650' FEL

AT TOP PROD. INTERVAL: Same as above

AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other) ☐

SUBSEQUENT REPORT OF:

APR 13 1983

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

OTD 4278', OPBTD 3800'. It is proposed to plug and abandon this well in the following manner:

1. MIRU pulling unit. ND WH. NU BOP. POOH w/rods & tbg.
2. RIH/tbg. to approximately 3800'. Spot a 17 sack cmt. plug across TOL. CHC. POOH to approximately 2900' & spot a 70 sack cmt. plug across base of salt. POOH.
3. RU WL. Perf. 2 0.46" sqz. holes @ approximately 1200'. POOH.
4. RIH w/cmt. retainer & tbg. to approximately 100' above the sqz. holes.

Subsurface Safety Valve: Manu. and Type SEE REVERSE SIDE Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Elmer Stutz REGION OPERATIONS
TITLE MANAGER - PROD. DATE 4-8-83

APPROVED

(This space for Federal or State office use)

APPROVED BY PETER W. CHESTER

CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

APR 14 1983

SEE REVERSE SIDE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-166

Circ. cmt. to surface and sqz. top of salt. Dump an 85 sack cmt. plug on top of retainer. POOH to approximately 300' and spot a 300' cmt. plug to surface. POOH.

5. NDBOP. CO WH. Install a dry hole marker to designate a plugged and abandoned location.

RECEIVED
APR 15 1983