

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

(Form C-102)
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O. C. C.

MISCELLANEOUS NOTICES Nov 11 3 53 PM '63

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Midland, Texas

November 8, 1963

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Sohio Petroleum Company

Williams

Well No. **1**

I

(Company or Operator)

NE **SE** **6** **18-S** **33-E** **Corbin** **Lea** **County.**

(40-acre Subdivision)

NMPM,

Pool

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed that the well be plugged in the following manner:

1. Place 25-sack cement plug from present plug at float collar in 5½" casing at approx. 4150' up to approx. 3950'.
2. Fill hole with mud laden fluid.
3. Determine stuck point of 5½" casing and cut off casing above it.
4. Place 20-sack cement plug at top of stub with bottom of plug being 50' into stub.
5. Place 20-sack cement plug at base of surface pipe.
6. Place 10-sack cement plug at surface.
7. Place regulation 4' steel marker four feet above ground level.

Copies of letter notifying offset operators are attached.

Approved....., 19.....
Except as follows: - /

Approved
OIL CONSERVATION COMMISSION

By *Leslie A. Colman*

Title.....

SOHIO PETROLEUM COMPANY

Company or Operator

By

J. H. Walters

Position

Assistant District Superintendent

Send Communications regarding well to:

Name **Sohio Petroleum Company**

Address **P. O. Box 3167, Midland, Texas**