

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ WIW
well well
2. NAME OF OPERATOR
Mobil Oil Corporation
3. ADDRESS OF OPERATOR
9 Greenway Plaza Ste 2700, Hou., TX 77046
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310'/FEL & 1650'/FNL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

Corrected Report

(NOTE: Report results of multiple completion or zone change on Form 9-330.1)

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 4318'. OH 4304 - 4318', pf. 4270 - 4302'; 8" csg. @ 1568', 5-1/2" csg. @ 9304', 2" tbg set in pkr. @ 4224', bottom @ 4252'. M.I., RU DA & S Well Service 4/9/77. POH w/ pkr & 2" tbg. Made trip w/bit & csg. scraper to 4170', POH; Set cmt. retainer @ 4170', test tbg. to 3000# - OK; sqzd. Queen perfs & OH w/75x cmt (4318-4170'). Pressured to 2300#, spotted 5x on top of retainer @ 4170'. Pulled up 4 jts; circ. to 9.5# MLF. Ran FPI, 5-1/2" csg free @ 1995'; cut @ 1984', LD 62 jts. Spotted 35x 2631-2930'. Pulled up to 2025'; spotted 60x 2025-1759'. Spotted 100x Class C 1617-1333', POH LD tbg., installed cellar on 8" csg., pressured to 850#. Shot 4 holes @ 500'. Pumped in 340x class H cmt.; 160x in form., 180x inside 8" from 500' - surface. Installed marker. RR 4:30 pm, 4/18/77.
FINAL REPORT

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Virginia Howard TITLE Authorized Agent DATE 6/13/79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JUL 13 1979
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well is conditioned for final inspection looking to approval of the abandonment.

GPO : 1975 O - 214-140

RECEIVED
JUL 17 1979
O.C.D. HOBBS, OFFICE