

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLE  
(Other instructions  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-0997

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

New Mexico Federal E

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

E. K. Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

28-T18S-R33E

12. COUNTY OR PARISH 13. STATE

Lea

N. M.

1. OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR  
Aztex Oil & Gas Company

3. ADDRESS OF OPERATOR  
c/o Hobbs Pipe & Supply Company, Box 2010, Hobbs, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FSL & 660' FEL, Section 28, T18S, R33E

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF   
FRACTURE TREAT   
SHOOT OR ACIDIZE   
REPAIR WELL   
(Other)

PULL OR ALTER CASING   
MULTIPLE COMPLETE   
ABANDON\*   
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF   
FRACTURE TREATMENT   
SHOOTING OR ACIDIZING   
(Other)

REPAIRING WELL   
ALTERING CASING   
ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

WELL WAS PLUGGED & ABANDONED AS FOLLOWS:

1. Loaded hole with mud-laden fluids.
2. Spotted 35 Sx cement plug 4250'-4400' to cover perforations.
3. 7" casing parted. Recovered 15 jts. (Est. 450') 7" Casing.
4. Could not catch 7" casing left in hole with spear. Hole caving badly.
5. Ran tubing. Spotted 50 Sx cement plug 200'-250' across 13-3/8" casing shoe @ 244'.
6. Spotted 10 Sx surface plug with marker.

WELL WAS PLUGGED AND ABANDONED ON 6/1/73.

18. I hereby certify that the foregoing is true and correct

SIGNED RM Williams

TITLE Agent, Hobbs Pipe & Supply

DATE 6/10/75

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

APPROVED

AUG 20 1975

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side