

Indian Agency.....

(SUBMIT IN TRIPLICATE)

U. S. Land Office **Las Cruces**

UNITED STATES

Lease or permit No. **029414**

Allottee.....

DEPARTMENT OF THE INTERIOR

S.W. Lodewick

Lease No.....

GEOLOGICAL SURVEY

DUPLICATE

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<b>X</b>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Wink, Texas November 4, 1938

S.W. Lodewick

Well No. 1 is located 660 ft. from DNK line and 1980 ft. from E line of sec. 34SE-1/4 of Sec. 34  
(1/4 Sec. and Sec. No.)18 S.  
(Twp.)33 E  
(Range)N.M.P.M.  
(Meridian)Wildcat

(Field)

Lea County

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3759 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth - 4295' Sand and Lime. At this depth salt water rose in the hole 500' and could not be lowered more than 150' by bailing approximately 6 barrels per hour for six hours. The water was encountered from 4290' to 4295'. We propose to plug and abandon this well as follows.

Will plug back with rock to approximately 4280' and drive 300' of lead wool on top of the rock at this point to plug off the water. Ten sacks of cement will be spotted on top of the lead wool. The hole will be filled with mud to the bottom of the 7" at 3870' and 10 sacks of cement spotted in the bottom of the pipe. After pasting and pulling approximately 3100' of 7" pipe the hole will be mudded to the bottom of the 9-5/8" casing and 10 sacks of cement spotted there. After mudding to the surface a 4" pipe marker will be cemented with 10 sacks.

Company The Texas CompanyAddress Drawer KWink, TexasBy [Signature]Title District Superintendent.

