Form C -103

OTHER 7. Describe Proposed or Completed Operations (Clearly state all pertinent tortils, and give pertinent dates, including estimated date of starting any propose work) see Rule 1103. 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUST BLING ALD 24 PROGRING OBERATIONS FOR THE CHOST 1 hereby certify that the Information above is tree and complete to the best of my knowledge and belief.	SUNDRY NOTICES AND REPORTS ON WELLS SOUND SUNDRY NOTICES AND REPORTS ON WELLS SOUND SUPPLY	SANTA FE	NEW HE	NICO 014		Form C-103 Supersedes Old
SUNDRY NOTICES AND REPORTS ON WELLS 1. First CD 3 distriction No. 1. Part CD 4 distriction No.	DEFINITION SUNDRY NOTICES AND REPORTS ON WELLS SUBSTITUTE AND REPORT OF WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUBSTITUTE AND REPORT OF WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUBSTITUTE AND REPORT OF WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUBSTITUTE AND REPORT OF WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORT ON WELLS SUBSTITUTE AND REPORT OF THE MEAN AND REPORT OF T	FILE	THE WINE	A 150 OIL CONSERV	ATION COMMISSION	Effective 1-1-65
Since Of a data Legan No. SUNDRY NOTICES AND REPORTS ON WELLS SUBJECT NOTICES AND REPORTS ON WELLS CAMPIE TO A SUBJECT NOTICES AND REPORTS ON WELLS CAMPIE TO A SUBJECT NOTICES AND REPORTS ON WELLS CAMPIE TO A SUBJECT NOTICES AND REPORTS ON WELLS CAMPIE TO A SUBJECT NOTICES AND REPORTS ON WELLS SUBJECT NOTICES AND REPORTS ON TO Indicate A sure of Notice. Report or Other Data SUBJECT NOTICES AND REPORTS OF THE NOTICE TO A SUBJECT NOTICES AND REPORTS OF THE NOTICE AND REPORTS OF THE NOTICES AND REPORTS OF THE NOTICES AND REPORTS OF THE NOTICE AND REPORTS OF TH	SUNDRY NOTICES AND REPORTS ON WELLS Shate Oil 6 Gas Leas B-1520 AND STATE ASSOCIATION OF THE PROPERTY OF THE PROPERTY SOLUTION OF THE PROPERTY S					
SUNDRY NOTICES AND REPORTS ON WELLS B-1520 SUNDRY NOTICES AND REPORTS ON WELLS OF SEASON WITH STANDARD STAND	SUNDRY NOTICES AND REPORTS ON WELLS Sundry					I Y
SUNDEY NOTICES AND REPORTS ON WELLS Section Section	SUNDRY NOTICES AND REPORTS ON WELLS See that processes received because the control of the cont	OPERATOR				
The coll persons of Control of the Coll of	SO NOT ARE THE DESCRIPTION OF SECURITY AND REPORTS ON WELLS STATE OF THE SECURITY AND SECURITY	CLIAL	IDDY NOTICE			B-1520
ALTERNOOF COMMISSION HOLD IN SECURE 113. Pull 2-3/8" C.L. tubing and packer @ 4577'. Run 5-1/2" common treatment on workstring and set @ 4600+. Pull 2-3/8" C.L. tubing and packer @ 4577'. Run 5-1/2" common treatment on workstring and set @ 4600+. Sound tubing common treatment on workstring and set @ 4600+. Pull 2-3/8" C.L. tubing and packer @ 4577'. Run 5-1/2" common treatment on workstring and set @ 4600+. Sound tag common top. Load hole with 9,56/9al. + mud ladened fluid. Pull casing. Run bind and packer pull and spot 100sx Class "H" neat coment. Run common to the set of the set of my knowledge and builed. Run common to the set of my knowledge and builed. Run common to the set of the set of my knowledge and builed. Run common the information above is tope and complete to the buil of my knowledge and builed. Run common the information above is tope and complete to the buil of my knowledge and builed. Run common the information above is tope and complete to the buil of my knowledge and builed. Run common the information above is tope and complete to the buil of my knowledge and builed. Run common the information above is tope and complete to the buil of my knowledge and builed. Run common the information above is tope and complete to the buil of my knowledge and builed. Run common the information above is tope and complete to the buil of my knowledge and builed. Authorized Agent 7/29/76	Section Composition Comp	(DO NOT USE THIS FORM FOR USE "APPLI	PROPOSALS TO DRILL OR TO	REPORTS ON WEL	LS	
Attended Commission Learner of Commission Active of Commission P. D. Box 633, Midland, TX 79701 S. Found of Commission P. D. Box 633, Midland, TX 79701 S. Found of Commission P. D. Box 633, Midland, TX 79701 S. Found of Commission Fast II. First on Commission II. First on Commission Fast II. First on Commission II. First on Commis	**************************************	014		RM C-101' FOR SUCH PRO	POSALS.	
Mobil Oil Corporation A Chiese of pressure P. O. Box 633, Midland, TX 79701 4. Location of Media Least Link, Section 11 Check Appropriate Box To Indices the state of Notice, Report of Other Data NOTICE OF INTENTION TO: Check Appropriate Box To Indices the state of Notice, Report of Other Data SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: PLACE AND ABANT X CHECKER STATE CHIEF THE STATE OF THE STA	Mobil Officers of Formers 1. Addition of Formers P. O. 805 633, Midland, TX 79701 4. Location of Well Whit ceres 0 660 East 111 12-5 ADDITION Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Report of Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Notice, Report of Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report of Other Data Subsequent Notice, Report of Other Data Subsequent Notice, Report of Other Data Subsequent Notice, Report of Notice, Report of Notice, Report of Notice, Report of Other Data Subsequent Notice, Report of Notice Report of No	WELL WELL	OTHER- WIW			7. Unit Agreement Name
Bridges State P. O. Box 633, Midland, TX 79701 4. Location of Med. 4. Location of Med. 4. Location of Med. 5. Submit State East 11 17-5	Bridges State P. O. 80x 633, Midland, TX 79701 S. Locution of Well Letter 0 660 Check Appropriate Box To Indicate No. 1980 Check Approved Check Indicate No. 1980 Check Approved Check Indicate Indicate Indicate No. 1980 Check Approved Check Indicate Indi	Mobil Oil Corporatio)n			9. Farm or Lease Name
South 1980 Least Certise 0 660 Check Appropriate Box To Indicate Notice, Report of Other Data Subsequent Report of Notice, Report of Other Data Subsequent Report of Notice Report of Notice Report of Other Data Subsequent Report of Notice Report of Notice Report of Other Data Subsequent Report of Notice Report of N	Location of Kill Location of Kill Location of Kill Location of Kill Least Line, Section Li	3. Address of Operator				•
East 10 1980	East 17-5	P. U. Box 633, Midia	nd, TX 79701			9. Well No.
The comment retainer on workstring and packer @ 4577'. Runs 2-1/2" comment retainer on workstring and set @ 4600+. Squeeze San Andres perfs (4564'-4692') with 50 sx Class "H" neat cement. MOC and tag cement top. Load hole with 9.5#/gal. + mud ladened fluid. Cut 5-1/2" casing at 1700'+. Pull casing. Cut 5-1/2" casing at 1700'+. Pull out workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the pull casing. Cut 5-1/2" casing at 1700'+. Pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the pull casing. Load hole with 9.5#/gal. + mud ladened fluid. The Comment of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the pull casing. Load hole with 9.5#/gal. + mud ladened fluid. The Comment of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the pull casing. Load hole with 9.5#/gal. + mud ladened fluid. The Comment of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the score of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the score of the score of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the score of the s	The complete Proposed or Completed Operations (Clearly state all pertinent Services and Services		660			1
The comment retainer on workstring and packer @ 4577'. Runs 2-1/2" comment retainer on workstring and set @ 4600+. Squeeze San Andres perfs (4564'-4692') with 50 sx Class "H" neat cement. MOC and tag cement top. Load hole with 9.5#/gal. + mud ladened fluid. Cut 5-1/2" casing at 1700'+. Pull casing. Cut 5-1/2" casing at 1700'+. Pull out workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the pull casing. Cut 5-1/2" casing at 1700'+. Pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the pull casing. Load hole with 9.5#/gal. + mud ladened fluid. The Comment of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the pull casing. Load hole with 9.5#/gal. + mud ladened fluid. The Comment of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the pull casing. Load hole with 9.5#/gal. + mud ladened fluid. The Comment of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the score of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the score of the score of the pull casing. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. The Comment of the score of the s	The Last Link, SECTION 15. Elevation (Show of Long, DE, RT, GR, etc.) 16. Check Appropriate Box To Indicate the second of the Data Subsequent Report of Cher Data Subsequent Report of Subsequent R	UNIT LETTER	FEET FROM 1	South	1980	Vacuum Coastant Of
Check Appropriate Box To Indicate to the best of Notice, Report or Other Data NOTICE OF INTENTION TO: Check Appropriate Box To Indicate to the best of my knowledge and better. Check Appropriate Box To Indicate to the best of my knowledge and better. ALTERING CASING Check Appropriate Box To Indicate to the best of my knowledge and better. Check Appropriate Box To Indicate to the best of my knowledge and better. AUCH 103. Check Appropriate Box To Indicate to the best of my knowledge and better. AUCheck Box To Check Casing Check Appropriate Box To Indicate to the best of my knowledge and better. Authorized Agent 12. Country Lea 12. Country Lea 12. Country Lea Check Appropriate Box To Indicate to the best of my knowledge and better. Authorized Agent 12. Country Lea 12. Country Lea 13. Erect monument ALTERING CASING ALTERING	Check Appropriate Box To Indicate The proposed of Cherty state of Notice, Report of Other Data Subsequent Report of Subsequent Report of Subsequent Report of Cherty State of Notice of Intention To: Proceeding Proceed of Completed Continue of State of	East East	11	77 C	FEE	T FROM Vacuum Grayburg SA
Check Appropriate Box To Indicate to the best of Notice, Report or Other Data NOTICE OF INTENTION TO: Check Appropriate Box To Indicate to the best of my knowledge and better. Check Appropriate Box To Indicate to the best of my knowledge and better. ALTERING CASING Check Appropriate Box To Indicate to the best of my knowledge and better. Check Appropriate Box To Indicate to the best of my knowledge and better. AUCH 103. Check Appropriate Box To Indicate to the best of my knowledge and better. AUCheck Box To Check Casing Check Appropriate Box To Indicate to the best of my knowledge and better. Authorized Agent 12. Country Lea 12. Country Lea 12. Country Lea Check Appropriate Box To Indicate to the best of my knowledge and better. Authorized Agent 12. Country Lea 12. Country Lea 13. Erect monument ALTERING CASING ALTERING	Check Appropriate Box To Indicate the properties of Notice, Report or Other Data Subsequent Report of Subsequent R	LINE, SEC	T10N 70V	VNSHIP 1/-5	RANGE 34-E	NMPM.
Check Appropriate Box To Indicate the present of Notice, Report or Other Data Subsequent Report of Notice of Intention to: **REMFORM REVISIONAL WORK** **PLIC AND ABANDON NOTICE OF INTENTION TO: **PLIC AND ABANDON NOTICE OF INTENTION TO: **PLIC AND ABANDON NOTICE OF INTENTION TO: **PLIC AND ABANDON NEW CHANGE PLANS **OFFICIAL WORK** **ALTERING CASING PLIC AND ABANDONMENT** **PLIC AND ABANDONMENT**	Check Appropriate Box To Indicate the present of Notice, Report or Other Data Subsequent Report of Intention to: Page 11					
NOTICE OF INTENTION TO: NOTICE OF INTENTION T	NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK TEMPORABLY ABANDON PULL OR ALTER CASING OTHER 7. Describe Proposed of Completed Operations (Clearly state all pertinest levels, and give pertinest dates, including estimated date of starting a work) SEE RULE 1103. 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUST B. NO ALD 14 PLOCATION OFFICATIONS FOR THE CLOST Thereby certify that the information above is true and complete to the bast of my knowledge and belief. Authorized Agent 7/29/76			4036 GR	1, On, etc.)	
SUBSEQUENT REPORT OF: TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 7. Describe Proposed or Completed Operations (Clearly state al' pertison' Craffic, and give pertisent dates, including estimated date of sturting any propose unork) see Rule 1 103. 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUST BE NO MED 24 PLOGENS OF APPROVED. Thereby certify that the information above is true and complete to the basi of my knowledge and belief. Authorized Agent 7/29/76	SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PULL OR ALTER CASING CHANGE PLANS CHAN	Check	Appropriate Box T	O Indicate Nature	of Varian D	Lea
PLUG AND ABANDON TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 7. Describe Processed or Completed Operations (Clearly state al' pertines' Livrils, and give pertinent dates, including estimated date of starting any propose works see Rule 1703. 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 13. Erect monument and clear location. THE COMMISSION MUST BE NO MED TO ALL PLOSES OF TO SEE APPROVED. 1 Intereby certify that the information above is true and complete to the brist of my knowledge and belief. Authorized Agent 7/29/76	TEMPORARILY ABANDON TEMPORARILY ABANDON OTHER OTHER 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUST BLING DID NA PLOGENS FOR THE CLOST TO SE APPROVED. 14. Authorized Agent 7/29/76	NOTICE OF	INTENTION TO:	!	Super o	or Other Data
PULL OR ALTER CASING OTHER 7. Describe Proposed or Completed Operations (Clearly state al' pertinent families, and give pertinent dates, including estimated date of starting any propose work) see RULE 1703. 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 13. Erect monument and clear location. THE COMMISSION MUST B. NO MID 24 PUCKING OPERATIONS FOR TH. CHO. Thereby certify that the information above is true and complete to the b-st of my knowledge and better. Authorized Agent 7/29/76	TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 7. Describe Proceed or Completed Operations (Clearly state al' pertinent tertiles, and give pertinent dates, including estimated date of starting a long of the loss. 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUST BE NO SED 24 PLOGING OFFRATIONS FOR THE CLEAR THE COMMISSION MUST BE NO SED 24 PLOGING OFFRATIONS FOR THE CLEAR Authorized Agent 7/29/76	PERFORM REMEDIAL		ļ		UENT REPORT OF:
OTHER OT	OTHER 7. Describe Proceed or Completed Operations (Clearly state al' pertinent invits, and give pertinent dates, including estimated date of starting a unork) SEE RULE 1103. 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUST BE NO MED 14 PLUGGING OURATIONS FOR THE CHORS TO BE APPROVED. 1 hereby certify that the information above is true and complete to the base of my knowledge and belief. Authorized Agent 7/29/76		PLUG AN	TE ABANDON X ROME	DIAL WCRK	¬ .
7. Describe Proceed or Completed Operations (Clearly state al' persinent livrils, and give persinent dates, including estimated date of starting any propose work) see RULE 1103. 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUST BLING AED 24 PLUCEING OBERATIONS FOR THE CLOSS Thereby certify that the information above is tree and complete to the best of my knowledge and belief. Authorized Agent 7/29/76	7. Describe Proceed or Completed Operations (Clearly state al' pertinent lartils, and give pertinent dates, including estimated date of starting a 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. 14. FIE COMMISSION MUST BLAC VID 24 PLOCING OF TATIONS FOR THE STONA GO OF TO SEE APPROVED. 14. Authorized Agent 7/29/76	<u></u>		COMP	IENCE DRILLING OPNS.	
7. Describe Proceed or Completed Operations (Clearly state al' pertinent larils, and give pertinent dates, including estimated date of starting any propose unit work) SEE RULE 1703. 1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUSI BLING ALD 24 PLUGGING OBERATIONS FOR THE CLOSS. The COMMISSION MUSI BLING ALD 24 PLUGGING OBERATIONS FOR THE CLOSS. Authorized Agent 7/29/76	7. Describe Processed or Completed Operations (Clearly state al' pertinent large), and give pertinent dates, including estimated date of starting a line in the process of		CHANGE	PLANS CASIN	G TEST AND CEMENT JOB	PLUG AND ABANDONMEN
1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUSI BLAC MED 24 PLUGGING OFFRATIONS FOR THE CIGHT 10 SS APPROVED. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. Authorized Agent 7/29/76	1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set losx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUST BL NO VIED ON PLUGGING OVERATIONS FOR TH CLOS TO SE APPROVED. Authorized Agent 7/29/76	OTHER				
1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUSI BLAC MED 24 PLUGGING OFFRATIONS FOR THE CIGHT 10 SS APPROVED. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. Authorized Agent 7/29/76	1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set losx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUST BL NO VIED ON PLUGGING OVERATIONS FOR TH CLOS TO SE APPROVED. Authorized Agent 7/29/76					
1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set 10sx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION MUSI BLAC MED 24 PLUGGING OFFRATIONS FOR THE CIGHT 10 SS APPROVED. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. Authorized Agent 7/29/76	1. Pull 2-3/8" C.L. tubing and packer @ 4577'. 2. Run 5-1/2" cement retainer on workstring and set @ 4600+. 3. Squeeze San Andres perfs (4664'-4692') with 50 sx Class "H" neat cement. 4. Pull out of retainer and spot 5 sx on top of retainer. 5. WOC and tag cement top. 6. Load hole with 9.5#/gal. + mud ladened fluid. 7. Pull tubing. 8. Cut 5-1/2" casing at 1700'+. 9. Pull casing at 1760'+ and spot 100sx Class "H" neat cement. 10. Run workstring to 1760'+ and spot 100sx Class "H" neat cement. 11. WOC-check cement top to see that it is not less than 1580'. 12. Set losx surface plug with Class "H" neat cement. 13. Erect monument and clear location. THE COMMISSION AUSI BLING VIDEOR PLUGGING OF TO THE SIGNAL OF TO THE SIGNAL OF TO THE SIGNAL OF TO SEAPPROVED. Authorized Agent 7/29/76	7. Describe Proposed or Completed C	perations (Clearly state o	il! pertinent i mil	,	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. Authorized Agent 7/29/76	Authorized Agent TITLE PROVED BY TITLE	3. Squeeze San Andr 4. Pull out of reta 5. WOC and tag ceme 6. Load hole with 9 7. Pull tubing. 8. Cut 5-1/2" casin 9. Pull casing. 10. Run workstring to 11. WOC-check cement 12. Set losx surface 13. Erect monument an THE COMMAN HOURS AND PERSONNE OF	res perfs (4664' ainer and spot 5 ainer and spot 6 ainer	vorkstring and 1-4692') with 5 sx on top of ladened fluid. ot 100sx Class t it is not less "H" neat cement on.	oO sx Class "H" retainer. "H" neat cement ss than 1580'. ent.	: .
Authorized Agent 7/29/76	Authorized Agent 7/29/76	C SE APPRO	DVED TOK IF	i C-103		personal of the
Authorized Agent 7/29/76	Authorized Agent 7/29/76				C-1	
DATE	ROYED BY	. I hereby certify that the information a			C-1	
3 May 7 1	TITLE	1 / 1000		e to the bast of my know	vledge and belief.	7/29/76
TITLE AND THE STATE OF THE STAT	NDITIONS OF APPROVAL, IF ANY:	NED / MC/	above is true and complete	e to the bast of my know	vledge and belief.	7/29/76