

FORMATION RECORD

| FROM | TO | THICKNESS IN FEET | FORMATION |
|------|------|----------------------|-------------------------|
| 0 | 33 | 33 | Caliche |
| 33 | 210 | 177 | Sand & Clay |
| 210 | 360 | 150 | Red Rock |
| 360 | 790 | 430 | Red Bed |
| 790 | 1054 | 264 | Red Rock |
| 1054 | 1152 | 98 | Red Rock & Sandy Shells |
| 1152 | 1332 | 180 | Red Bed & Shells |
| 1332 | 1540 | 208 | Red Rock |
| 1540 | 1650 | 110 | Anhydrite |
| 1650 | 2763 | 1113 | Anhydrite & Salt |
| 2763 | 3080 | 317 | Anhydrite & Gyp |
| 3080 | 3135 | 55 | Anhydrite |
| 3135 | 3185 | 50 | Anhydrite & Gyp |
| 3185 | 3260 | 75 | Broken Sand |
| 3260 | 3337 | 77 | Red Sand & Anhydrite |
| 3337 | 3390 | 53 | Anhydrite & Gyp |
| 3390 | 3551 | 161 | Anhydrite |
| 3551 | 3702 | 151 | Anhydrite & Gyp |
| 3702 | 3985 | 283 | Anhydrite |
| 3985 | 4100 | 115 | Anhydrite & Lime |
| 4100 | 4710 | 610 | Lime |

4710' T. D. - Lime

Deviation tests as follows:

360' - 0°
 750' - 1/4°
 1275' - 0°
 1760' - 0°
 2500' - 0°
 3015' - 1/4°
 3506' - 3/4°
 4066' - 3/4°