

**NEW MEXICO STATE LAND OFF.
OFFICE OF THE STATE GEOLOGIST
SANTA FE, NEW MEXICO**

MISCELLANEOUS REPORTS ON WELLS

Submit this report in duplicate to the State Geologist or proper Oil and Gas Inspector within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of water shut-off, result of abandonment of well, and other important operations, even though the work was witnessed by the State Geologist or Oil and Gas Inspector. Reports on minor operations need not be signed and sworn to before a notary public, but such operations should be witnessed by an Oil and Gas Inspector if possible. Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF SHOOTING WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF WATER SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF ABANDONMENT OF WELL			

Hobbs, New Mex. 4-11-33

PLACE DATE

Mr. E. H. Wells State Geologist,
Santa Fe, N. Mex.

Following is a report on the work done and the results obtained under the heading noted above at the
The California Company - McKinley Well No. 2 in the

~~N. 1/4~~ COMPANY OR OPERATOR of Sec. 20, T. 18-S LEASE, R. 38-E, N. M. P. M.,
Hobbs Oil Field, Lea County.
4-9-33 and 4-10-33

The dates of this work were as follows:

Notice of intention to do the work was ~~not~~ submitted ~~on Form SG-103~~ verbally to ~~Mr. Hunter~~ ~~4-3-33~~, 19____, and approval of the proposed plan was ~~not~~ obtained. (Cross out incorrect words.) Form SG-103 was submitted 4-11-33.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On 4-9-33 a 30-minute pressure test of 7" casing was witnessed and approved by State Oil & Gas Inspector, J. D. Hunter. On 4-9-33 top of cement plug in 7" casing was found at 4021' and the shoe at 4054'. On 4-10-33 a Halliburton tester was run into hole on dry 3" drill pipe with a 38' anchor the top 3' of which was perforated. Packer on tester was set in 7" casing at 4020'. The valve on Halliburton tester was opened for 1 hour during which time the fluid level between the drill pipe and casing did not change, and no fluid entered the drystring of 3" drill pipe. The test was witnessed and shut-off approved by Mr. J. D. Hunter, State Oil & Gas Inspector.

Subscribed and sworn to before me this
7th day of August, 1933.

[Signature]
NOTARY PUBLIC.

My commission expires June 1, 1935

Remarks:

I hereby swear or affirm that the information given above is true and correct.

Name *[Signature]*
Position General Superintendent
Representing The California Company
Address Midland, Texas

COMPANY OR OPERATOR.

