

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____ 1360	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____ 1580	T. Strawn _____ 12050	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____ 2780	T. Atoka _____ 12367	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2965	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Manefee _____	T. Madison _____
T. Queen _____ 4180	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____ 4660	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 4792	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____ 10682	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1360	1360	Red Sand & Shale				
1360	1580	220	Anhydrite				
1580	2780	1200	Salt				
2780	2965	185	Dolomite & Anhydrite				
2965	4180	1215	Sand & Dolomitic Sand				
4180	4660	480	Sand, Dolomite and Anhydrite				
4660	4800	140	Anhydritic Dolomite				
4800	5596	796	Dolomite and Sand				
5596	7419	1823	Sand, Shale & Limestone				
7419	10682	3263	Limestone and Sand				
10682	12050	1368	Limestone and Shale				
12050	12367	317	Limestone, Chert and Shale				
12367	12718	351	Shale and Sand				
12718	13011	230	Limestone and Shale				
13011	13650	639	Sand and Shale				

RECEIVED

APR 20 1970

OIL CONSERVATION COMM.
13210