

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0556094

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

CORRECTED REPORT

2. NAME OF OPERATOR

Burleson & Huff

3. ADDRESS OF OPERATOR

P. O. Box 935, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

330' from the North & East line of Section 32

T-18-S, R-32-E, Lea County, New Mexico

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Superior Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR DLK. AND SURVEY OR AREA

Sec. 33, T-18-S, R-32-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3713.4 GR

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following plugs were set as approved:

100' cement plug Top of Queen - 3900' - 4000'

100' cement plug base of salt - 2600' - 2700' - corrected

50' cement plug top of salt - 1150' - 1200'

50' cement plug base of surface pipe - 700' - 750'

10' sx plug at surface

D & A marker - mud placed in hole between plugs.

You will be notified when the location is leveled so it may be inspected.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Partner

DATE

2-9-73

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

APR 18 1974

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side